

# K3A2U2, AL Universal Terminal, 3 Conductor, #14-2 AWG Str, 2-Hole, 5/16" Stud, .88" Spacing, 3 Screws, Al/Cu Rated



By Burndy  
Catalog # [K3A2U2](#)

Aluminum Universal Terminal, 3 Conductor, 2 Hole, 14-2 AWG (Str), 5/16" Stud, .88" Stud Hole Spacing, 3 Screws, Al/Cu Rated, Tin Plated.

## Features

- Constructed from high strength aluminum alloy
- Electro tin plating proving low contact resistance

## Application

For Aluminum and Copper Conductors

## General

Catalog Number	K3A2U2
Connector Type	Parallel Set-Screw
EU RoHS Indicator	Yes
Installation Torque	50 LBS/in
Recommended in-lb	
Material	Aluminum
Material - Hardware	Aluminum
Physical Attribute - Number of Holes	2
Physical Attribute - Number of Screws	3
Physical Attribute - Screw Type	Slot
Plated	Y
Plating Type	Tin plated
Sub Brand	UNIVERSAL TERM
Temperature Rating	194
Type	Bolted Lugs & Terminals
UPC	781810370360
UPC 12 Digit	7818103703600

## Dimensions

Dimension - Bolt Hole Size inch	0.57 in
Dimension - Bolt Size fraction	5/16
Dimension - D inch	1.63 in
Dimension - Height fraction	5/8 in
Dimension - Height inch	0.62 in
Dimension - Height mm	15.7 mm
Dimension - Hole Size fraction	11/32
Dimension - Hole Size inch	0.34 in
Dimension - Hole Size mm	9 mm

Dimension - L Length Overall mm	55.62 mm
Dimension - Length Overall inch	2.19 in
Dimension - N inch	0.34 in
Dimension - Pad Width inch	1.64 in
Dimension - Stud Size inch	5/16 in
Dimension - Width fraction	1-59/100 in
Dimension - Width inch	1.64 in
Dimension - Width mm	40 mm

## Electrical Ratings

Rating - Minimum Voltage	600
--------------------------	-----

## Conductor Related

Conductor - AL Str Size	8 AWG;6 AWG;4 AWG;3 AWG;2 AWG
Conductor - AL Str Size Range	14-2 AWG
Conductor - Copper Str Size	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - Copper Str Size Range	14-2 AWG
Conductor Size	14-2 AWG
Conductor Type	<ul style="list-style-type: none"> <li>• AL C Str-Size</li> <li>• CU C Str-Size</li> </ul>
Number of Conductors	3

## Certifications And Compliance

Buy American Compliant	Contact Manufacturer
Certification - CSA Approved	Yes
Certification - UL Listed Direct Burial	No
Certified Listed	BABA Compliant (All status valid till December 2024)
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards	UL 486A-486B
Met	

Standards - RoHS Compliance EX  
Status  
UL Listed Yes

**Logistics**

Carton Quantity 216  
Minimum Pack Quantity 1

**Product Assets**

[3D Models - K3A2U2\\_MODEL-IGES](#)  
[3D Models - K3A2U2\\_MODEL-STEP](#)  
[3D Models - K3A2U2\\_MODEL-PDF](#)  
[Catalogs - BURNDY Master Catalog - Section A - Mechanical](#)  
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)  
[Product Cross Section Image\(s\) - BUR\\_K3AU\\_LineArt](#)  
[Sales Drawings - se210997](#)  
[Specifications - K3A2U2](#)



A Hubbell brand