

22779 - GE LED HID - Type B

LED50ED23.5M/740

- ☞ Open and Closed Rated
- ☞ Ballast Bypass required
- ☞ Damp
- ☞ Not suitable for air-tight explosive or hazardous fixtures
- ☞ For additional collateral click the link below: https://products.currentbyge.com/led-lamps-and-modules/led-replacement-for-hid

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	Medium Screw
Base Type	Screw-In
Body Color	Clear
Dimmable	No
Primary Application	Replacement for HID
Product Color	Clear
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	No
Lamp Count	1
Life in Years	17.1 yr
Requested Structure	Carton
Estimated Energy Cost per Year	16.06

PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	150
Initial Lumens-nominal	7500 lm
Color Rendering Index-CRI	70
Color Temperature	4000 K

PRODUCT INFORMATION

Product Code	22779
Description	LED50ED23.5M/740
Alternative Unit Of Measure	CASE
Standard Package Quantity	
Ean UPC	043168227797
Standard Package GTIN	10043168227794
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Case
UCC	
Alternative Unit Of Measure	EACH
Standard Package Quantity	
Ean UPC	043168227797
Standard Package GTIN	00043168227797
No Of Items Per Sales Unit	
No Of Items Per Standard Package	
Sales Unit	Each
UCC	

DIMENSIONS

Bulb Max Overall Length-MOL	7.7 in
-----------------------------	--------

ELECTRICAL CHARACTERISTICS

Voltage <Nom>	120 V
Rated power (Watts)	50 W