

# Product data sheet

## Characteristics

# XZCC20FCM30B

female, 1/2 20UNF, 3-pin, elbowed connector - cable gland Pg 7



### Main

Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Elbowed female connector 1/2 20 UNF, 3 pins
Collar material	Metal
Status LED	Without
Cable connection	Screw terminal 0.00 in <sup>2</sup> (0.75 mm <sup>2</sup> ) 0.12...0.24 in (3...6 mm)

### Complementary

Cable gland type	Pg 7
Cable connector fixing	Screw-on
[Ue] rated operational voltage	250 V AC
[In] rated current	4 A
Enclosure material	Plastic
Minimum insulating resistance	1000 GΩ
Contact resistance	8000 μOhm
Net weight	0.04 lb(US) (0.02 kg)

### Environment

IP degree of protection	IP67
Ambient air temperature for operation	-40...185 °F (-40...85 °C)

### Packing Units

Package 1 Weight	0.05 lb(US) (0.024 kg)
Package 1 Height	0.200 dm
Package 1 width	0.360 dm
Package 1 Length	0.400 dm

### Offer Sustainability


REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

**Contractual warranty**

Warranty	18 months
----------	-----------

Dimensions



- (1) Cable gland : no. 7 plastic (Pg 7)

---

Connections and Schemes

---

