

Product data sheet

Characteristics

9999D20

Contacteur, Definite Purpose, auxiliary contact, 3A at 120 VAC, 2 NO contacts, for 20A to 90A DPA contactors



Main

Product Range	DPA
Component type	Auxiliary Contact Module
Used with	contacteur

Complementary

Auxiliary contact composition	2 NO
Rated breaking capacity	3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 0.75 A 480 V AC inductive control circuit UL 508 0.6 A 600 V AC inductive control circuit UL 508 5 A <= 600 V AC resistive control circuit UL 508

Environment

Product Certifications	CSA[RETURN]UL Recognized
------------------------	--------------------------

Ordering and shipping details

Category	21762-9999 DISCOUNT CP1B
Discount Schedule	CP1B
GTIN	785901081319
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.70 in (1.778 cm)
Package 1 Width	1.80 in (4.572 cm)
Package 1 Length	3.70 in (9.398 cm)
Package 1 Weight	1.44 oz (40.823 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	25
Package 2 Height	4.60 in (11.684 cm)
Package 2 Width	4.60 in (11.684 cm)
Package 2 Length	10.40 in (26.416 cm)
Package 2 Weight	2.66 lb(US) (1.207 kg)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months
----------	-----------