



## Main

Range of Product	Lexium P, T
Product or Component Type	Delta 3 robot
Device short name	P2
Design	Compact

## Complementary

Number of axis	4
Operating position	Rotational 360°
Work envelope	0.00...31.50 in (0...800 mm) diameter 0.00...10.79 in (0...274 mm) vertical
Repeat accuracy	0.1 mm
Permanent permissible load	33.07 lb(US) (15 kg)
Maximum actuation speed	32.81 ft/s (10 m/s)
Maximum acceleration	393.70 Ft/S <sup>2</sup> (120 m/s <sup>2</sup> ) at 1 kg 295.28 ft/s <sup>2</sup> (90 m/s <sup>2</sup> ) at 1.5 kg
Net Weight	154.32 lb(US) (70 kg)
Range Compatibility	Lexium SH3 motor

## Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

## Ordering and shipping details

Category	18357-PACDRIVE ROBOTIC
Discount Schedule	PC52
GTIN	3606485399058
Returnability	No

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	53.15 in (135.0 cm)
Package 1 Width	47.24 in (120.0 cm)
Package 1 Length	39.37 in (100.0 cm)
Package 1 Weight	165.35 lb(US) (75.0 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes