



Main

| | |
|-----------------------|----------------------------|
| Product | Single Throw Safety Switch |
| Disconnect Type | Fusible disconnect |
| Number of Poles | 3 |
| Electrical Connection | Lugs |
| Duty Rating | Heavy duty |

Complementary

| | |
|---------------------------|--|
| Line Rated Current | 400 A |
| Factory Installed Neutral | None |
| Mounting Type | Surface |
| Voltage Rating | 600 V AC/DC |
| Motor power hp | 100 Hp at 480 V AC 50-60 Hz for 3 phase motors 250 Hp at 480 V AC 50-60 Hz for 3 phase motors 125 Hp at 600 V AC 50-60 Hz for 3 phase motors 350 Hp at 600 V AC 50-60 Hz for 3 phase motors 50 Hp at 250 V DC 50 hp at 600 V DC |
| Wire Size | AWG 1/0...750 kcmil copper or aluminium |
| Tightening torque | 550 lbf.in (62.14 N.m) (AWG 1/0...750 kcmil) |
| Height | 46.25 in (1174.75 mm) |
| Width | 26.25 in (666.75 mm) |
| Depth | 10.13 in (257.30 mm) |

Environment

| | |
|------------------|-------------------------------|
| Certifications | CSA |
| Enclosure Rating | NEMA 4/4X stainless steel 304 |

Ordering and shipping details

| | |
|-------------------|----------------------------------|
| Category | 00153-C,CH&CHU CANADA SW NON-NEG |
| Discount Schedule | DE1 |
| GTIN | 785901610304 |
| Returnability | Yes |
| Country of origin | US |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|--------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 12.80 in (32.5 cm) |
| Package 1 Width | 26.81 in (68.1 cm) |
| Package 1 Length | 50.71 in (128.8 cm) |
| Package 1 Weight | 153.99 lb(US) (69.85 kg) |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |