

Product data sheet

Characteristics

8903LXG60V85CFF4R6T

Contactor, Type L, multipole lighting, mechanically held, 30A, 6 pole, 600 V, 110/120 VAC 50/60 Hz coil, NEMA 1, +option



Main

| | |
|---------------------------|--------------------------------------|
| Product or Component Type | Mechanically Held Lighting Contactor |
| Range of Product | 8903LX |
| Control Circuit | Control circuit transformer |

Complementary

| | |
|------------------------|--|
| Control Voltage | 120 V AC 60 Hz secondary circuit 277 V AC 60 Hz primary circuit |
| Inrush power in VA | 180 VA 60 Hz 25 VA 50/60 Hz |
| Current Rating | 20 A tungsten 30 A fluorescent |
| Number of Poles | 6P 6 NO |
| Control Unit | Selector switch HAND-OFF-AUTO) |
| Pilot Light | No indicator |
| Control Circuit Fusing | 2 fuses primary circuit 1 fuse secondary circuit |
| Other Options | 2P relay (1 NO + 1 NC) |
| Electrical Connection | Screw-clamp terminals |
| Height | 11.89 in (302 mm) |
| Depth | 7.44 in (189 mm) |
| Width | 11.89 in (302 mm) |

Environment

| | |
|------------------------|------------------------------------|
| Enclosure Type | NEMA 1 painted sheet steel surface |
| Product Certifications | UL Listed[RETURN]CSA |

Ordering and shipping details

| | |
|-------------------|-------------------------|
| Category | 21322 - 8903 LX (NOT L) |
| Discount Schedule | CP1 |
| Returnability | No |
| Country of origin | MX |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| | |
|-----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|