


Heavy duty grade power receptacles

Product description

2-pole, 3-wire grounding
50A, 125V/AC
50A, 250V/AC



1253




1252

Design features

- Heavy gauge galvanized steel mounting strap for corrosion resistance
- For use with copper or aluminum wire
- Flush receptacles fit one-gang or two-gang enclosures
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom

Flush power receptacles

Rating	A	V/AC	Description	Color	Catalog no.	
50	125		NEMA 5-50R flush mount power receptacle, matching plug A41	BK	□ 1253	•
50	250		NEMA 6-50R flush mount power receptacle, matching plug S42	BK	□ 1254	•

Listed to UL498, file no. E15058; CSA certified to CSA C22.2, no. 42

Surface power receptacles

Rating	A	V/AC	Description	Color	Catalog no.	
50	250		NEMA 6-50R surface mount power receptacle, matching plug S42	BK	□ 1252	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Compatible wallplates / standard size for flush power receptacles

Description	Color suffix	Catalog no.	
Thermoset 1-gang wallplate for one power receptacle	A, B, V, W	□ 2068__	•
Thermoset 2-gang wallplate for one power receptacle	A, B, LA, V, W	□ 2168__	•


Listed to UL498, file no. E15058

Compatible wallplates / standard size for flush power receptacles

Description	Color	Catalog no.	
1-gang wallplate for one power receptacle	Stainless Steel	□ 93221	•
2-gang wallplate for one power receptacle	Stainless Steel	□ 93227	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42

Compatible wallplates / standard size for flush power receptacles

Description	Color suffix	Catalog no.	
Nylon 1-gang wallplate for one power receptacle	V	□ 5068	•
Polycarbonate 1-gang wallplate of one power receptacle	B, BK, V, W	□ PJ724__	
Polycarbonate 2-gang wallplate for one power receptacle	B, V, W	□ PJ703__	

Listed to UL498, file no. E15058

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), LA (Light Almond), V (Ivory), Stainless Steel, W (White).



Dimensional information: B-70 **Specification information:** Please visit www.cooperwiringdevices.com
Compliances, specifications and availability are subject to change without notice.

 Indicates NAFTA compliant - Page F-21