



## Main

Product or Component Type	Motor Circuit Protector
Trip Unit Technology	Thermal-magnetic

## Complementary

Rated Current	400 A
Number of Poles	3P
Breaking Capacity Interrupt Rating	42 KA at 240 V AC 30 KA at 480 V AC 22 KA at 600 V AC 10 KA at 125 V DC 10 kA 250 V DC
Rated Operational Voltage	600 V AC 250 V DC
Mounting Mode	Unit mount
Electrical Connection	Lugs load Lugs line
AWG Wire Gauge	AWG 1...600 kcmil (aluminium/copper) for 1 cable(s) AWG 1...250 kcmil (aluminium/copper) for 2 cable(s)
Terminal Type	AL400LA
Magnetic Hold Current	1500 A
Magnetic Tripping Current	3000 A
Height	11 in (279.40 mm)
Width	6 in (152.40 mm)
Depth	5.84 in (148.34 mm)
Tightening Torque	13 N.M for 42...304 mm <sup>2</sup> (AWG 1...600 kcmil) 13 N.m for 42...127 mm <sup>2</sup> (AWG 1...250 kcmil)

## Environment

Certifications	CSA IEC UL Listed
----------------	-------------------------

## Ordering and shipping details

Category	00935-LAL/LHL BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901358398
Package weight(Lbs)	16.51 lb(US) (7.490 kg)
Returnability	Yes
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------