

Product data sheet

Specifications



Floor standing polyester enclosure,
PanelSeT PLA, plain door,
completely sealed,
2000x750x420mm, IP65, IK10

NSYPLA2074G

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range	PanelSeT
Product name	PanelSeT PLA
Enclosure type	Multi-purpose
Product or Component Type	Suitable enclosure
Version	PLA
Nominal height	78.7 in (2000 mm)
Nominal width	29.5 in (750 mm)
Nominal depth	16.5 in (420 mm)
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 side part 1 rear panel 2 door

Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Solid front
Number of doors	2
Door opening side	Reversible 120 °)
Lock type	4 points lock, 5 mm double-bar
Accessibility for operation	Rear Front
Removable parts	Door by hinges Rear panel by fixing element
Material	polyester reinforced with fibreglass
color	Gray RAL 7035)
Standards	UL 508 A IEC 62208
NEMA Degree of Protection	NEMA 12 NEMA 3X NEMA 2 NEMA 5 NEMA 13 NEMA 3R NEMA 3 NEMA 3S NEMA 1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Certifications	DNV Marine Veritas UL/cUL listed
Electrical Insulation Class	Class II

Environment

IP degree of protection	IP65 IEC 60529 completely sealed)
IK degree of protection	IK10 IEC 62262 plain door)
Fire resistance	1760 °F (960 °C) IEC 62208
Ambient Air Temperature for Storage	-31...194 °F (-35...90 °C)

Ordering and shipping details

Category	US10ES180035
Discount Schedule	0ES1
GTIN	3606485435442
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	83.858 in (213.000 cm)
Package 1 Width	31.496 in (80.000 cm)
Package 1 Length	19.291 in (49.000 cm)
Package weight(Lbs)	145.505 lb(US) (66.000 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	513 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	240 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	131 kg CO2 eq.
Carbon footprint of the installation phase [A5]	22 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	120 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	1341ad4e-77b9-40e3-bab0-32043fbc5959
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes
Silicon free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	6
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration

Dimensions



Image of product in real life situation

