


Non-Insulated Stranded Conductor for Lightning Protection – LPC126RL250



- Provides a path to ground for lightning currents



Part Number	LPC126RL250
Certification Details	UL® 96
Material	Copper
Finish	Tinned
UL Conductor Class	Class II
Conductor Type	Ropelay
Number of Wires	28
Wire Diameter	1.63 mm
Diameter	11.9 mm
Length	76.2 m
Cross Section	58.31 mm ²
Unit Weight	0.172 kg
Certifications	UL
Standard Packaging Quantity	250'
UPC	78285661142
EAN-13	8711893099966

Equivalent Conductor Size	
Part Number	Conductor Size
LPC134xxx	2/0
LPC136xxx	3/0
LPC137xxx	4/0

Unit weight is per foot (0.3048 m).

Cut-to-order (CTO) lengths are available for an additional charge.

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.