



## Main

Product or Component Type	Industrial Control Transformer
Range of Product	EL

## Complementary

Phase	1 phase
Rated power in VA	100 VA
Primary Voltage	240 V 220 V 230 V
Secondary Voltage	110 V 120 V 115 V
Temperature rise	55 °C
Electrical Connection	Screw clamp terminals
Connector type	Lead 2001.31 ft (610 m)

## Environment

Product Certifications	UL Listed[RETURN]CSA[RETURN]CE
NEMA Degree of Protection	Not rated (open device)
Insulation temperature	221 °F (105 °C)

## Ordering and shipping details

Category	16208-9070 9070 AP,E,G,H,SB, T, TF, (ALL)
Discount Schedule	CP8
GTIN	3606486126349
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.50 in (8.89 cm)
Package 1 Width	3.88 in (9.855 cm)
Package 1 Length	4.00 in (10.16 cm)
Package 1 Weight	3.90 lb(US) (1.769 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------