

# XVUC43

Modular tower light, Harmony XVU, illuminated LED units, green, 60mm, blinking, IP65, 24V AC DC



## Main

|                                    |  |
|------------------------------------|--|
| Range of Product                   | Harmony XVU                                      |
| Product or Component Type          | Modular tower light                              |
| Beacon or indicator bank unit type | LED unit   |
| Mounting diameter                  | 2.36 in (60 mm)                                  |
| Component name                     | XVU  |
| Light source                       | LED, green                                       |
| Device Application                 | Machine tools<br>Packaging machine<br>Automotive |

## Complementary

|                                |   |
|--------------------------------|---|
| Signalling type                | Blinking  |
| Assembly style                 | Customer assembly, up to 5 units<br>Up to 4 units with buzzer |
| Material                       | PC (polycarbonate) V-2 UL 94<br>PC (polycarbonate) V-0 UL 94  |
| [Us] Rated Supply Voltage      | 24 V AC/DC  |
| Maximum power dissipation in W | 1.2 W   |
| Signalling type                | Blinking  |
| Length                         | 1.97 in (50 mm)   |
| Net Weight                     | 0.14 lb(US) (0.064 kg)  |

## Environment

|                                       |                            |
|---------------------------------------|----------------------------|
| Product Certifications                | UL[RETURN]CSA[RETURN]CE    |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C) |
| IP degree of protection               | IP65                       |
| Ambient Air Temperature for Operation | -13...122 °F (-25...50 °C) |
| Vibration resistance                  | 2 gn                       |

## Ordering and shipping details

|                   |                        |
|-------------------|------------------------|
| Category          | 22618-XVU TOWER LIGHTS |
| Discount Schedule | XV                     |
| GTIN              | 3606480886942          |
| Returnability     | Yes                    |
| Country of origin | ID                     |

## Packing Units

|                              |                    |
|------------------------------|--------------------|
| Unit Type of Package 1       | PCE                |
| Number of Units in Package 1 | 1                  |
| Package 1 Height             | 3.70 in (9.4 cm)   |
| Package 1 Width              | 3.70 in (9.4 cm)   |
| Package 1 Length             | 5.30 in (13.46 cm) |
| Package 1 Weight             | 4.94 oz (140 g)    |

|                              |                           |
|------------------------------|---------------------------|
| Unit Type of Package 2       | S03                       |
| Number of Units in Package 2 | 24                        |
| Package 2 Height             | 11.81 in (30 cm)          |
| Package 2 Width              | 11.81 in (30 cm)          |
| Package 2 Length             | 15.75 in (40 cm)          |
| Package 2 Weight             | 9.57 lb(US) (4.341 kg)    |
| Unit Type of Package 3       | P06                       |
| Number of Units in Package 3 | 192                       |
| Package 3 Height             | 29.53 in (75 cm)          |
| Package 3 Width              | 23.62 in (60 cm)          |
| Package 3 Length             | 31.50 in (80 cm)          |
| Package 3 Weight             | 115.65 lb(US) (52.456 kg) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |


---

## Illuminated LED Unit


---

### Dimensions

$\frac{\text{mm}}{\text{in.}}$



## Modular Tower Lights Mounting



| Drawing  | Part number          | Part name                    |
|----------|----------------------|------------------------------|
| A1       | -                    | Top cover                    |
| -        | Top cover (Silver)   |                              |
| A2       | XVUC9S               | Buzzer unit                  |
| XVUC9SQ  | Buzzer unit (Silver) |                              |
| A3       | XVUC23               | Green LED unit               |
| XVUC24   | Red LED unit         |                              |
| XVUC25   | Orange LED unit      |                              |
| XVUC26   | Blue LED unit        |                              |
| XVUC27   | White LED unit       |                              |
| XVUC28   | Yellow LED unit      |                              |
| A4       | XVUC29               | Multi-LED unit               |
| A5       | XVUC29P              | Multi-LED unit, Pulse signal |
| A6       | XVUC9V               | Sound unit                   |
| A7       | XVUC9VP              | Sound unit, Pulse signal     |
| A8       | XVUC020              | Extender                     |
| XVUC020Q | Extender (Silver)    |                              |
| A9       | XVUC21B              | DC body                      |

| Drawing   | Part number                                    | Part name   |
|-----------|--|---|
| XVUC21BQ  | DC body (Silver)                               |   |
| A10       | XVUC21M  | AC body NPN   |
| XVUC21MP  | AC body PNP                                    |   |
| XVUC21MQP | AC body PNP (Silver)                           |   |
| A11       | XVUZ06   | Flexible option                                       |
| A12       | XVUZ01   | Fixing Unit - Direct mounting (3 pins)                |
| XVUZ01Q   | Fixing Unit - Direct mounting (Silver,3 pins)  |   |
| XVUZ03    | Fixing Unit - Direct mounting (2 pins)         |   |
| XVUZ04    | Fixing Unit - Direct mounting (4 pins)         |   |
| A13       | XVUZ02   | Fixing Unit - Plate with Pole (100 mm)                |
| XVUZ02Q   | Fixing Unit - Plate with Pole (100 mm, Silver) |   |
| XVUZ400   | Fixing Unit - Plate with Pole (400 mm)         |   |
| XVUZ800   | Fixing Unit - Plate with Pole (800 mm)         |   |
| A14       | XVUZ05   | Fixing Unit - Plate with adjustment pole (100-385 mm) |
| A15       | XVUC43   | Green LED unit, Flash                                 |
| XVUC44    | Red LED unit, Flash                            |   |
| XVUC45    | Orange LED unit, Flash                         |   |
| XVUC46    | Blue LED unit, Flash                           |   |
| XVUC47    | White LED unit, Flash                          |   |
| XVUC48    | Yellow LED unit, Flash                         |   |
| A16       | XVUZ100T                                       | Fixing Unit - Metal bracket with pole (100 mm)        |
| XVUZ250T  | Fixing Unit - Metal bracket with pole(250 mm)  |   |
| XVUZ400T  | Fixing Unit - Metal bracket with pole (400 mm) |   |
| A17       | XVUZ12   | Fixing plate for use on vertical support - black      |

## Illuminated Units, Multi-LED and Audible Units Wiring



- (A) Fixing Unit
  - (1) Dimensions of Wiring size
  - (2) Push-in Wire Connectors
  - (3) Fuse : 2A ,250V
  - (4) Fuse : 0.5A , 125V
  - (5) Modular Tower Lights 24V AC/DC
  - (6) Modular Tower Lights 100...240V AC
- L1 to Illuminated LED Units  
L5 :