



Main

Range	PowerLogic
Product or Component Type	Remote display
Device Application	Human-machine dialogue application
Range compatibility	PowerLogic PowerLogic PM5000
Display Type	Backlit LCD

Complementary

Display colour	Monochrome
Display Resolution	128 x 128 pixels
Display size	67 x 62.5 mm
Information Displayed	Power Energy consumption Harmonic distortion Frequency Voltage Current
Messages display capacity	6 lines Graphic objects (bargraph, button, light...)
Local signalling	Communication LED Green) Programming indication LED amber)
Control type	4 x push-button
Connector Type	RJ45
Mounting Mode	Flush-mounted
Mounting support	Framework remote display
Width	3.78 in (96 mm)
Height	3.78 in (96 mm)
Embedding Depth	0.83 in (21 mm)
Projecting depth	1.06 in (27 mm)

Environment

IP degree of protection	IP52 IEC 60529
Relative humidity	5...95 % 99 °F (37 °C)
Operating altitude	0...9842.52 ft (0...3000 m)
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

Ordering and shipping details

Category	09778-POWERLOGIC PM5000 ACCESSORIES
Discount Schedule	PL1
GTIN	3606480761423
Returnability	Yes
Country of origin	IN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.76 in (7 cm)
Package 1 Width	3.94 in (10 cm)
Package 1 Length	3.94 in (10 cm)
Package 1 Weight	11.29 oz (320 g)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.