

Product data sheet

Characteristics

8501RS43V20

Plug in relay, Type R, miniature, 1 HP at 277 VAC, 15A resistive at 120 VAC, 11 blade, 3PDT, 3 NO, 3 NC, 120 VAC coil



Main

| | |
|---------------|-----------------|
| Product range | 8501R |
| Product type | Miniature Relay |
| Relay Type | Standard |

Complementary

| | |
|------------------------------|---|
| Mounting type | Socket |
| Contact composition | 3PDT |
| [Uc] control circuit voltage | 120 V AC |
| Pilot light | No indicator |
| Manual operator | Without test button |
| Horsepower rating | 0.5 120 V AC 1 277 V AC |
| Breaking capacity | 3 A 120 V AC inductive control circuit UL 508 1.5 A 240 V AC inductive control circuit UL 508 10 A 120 V AC resistive control circuit UL 508 6.67 A 277 V AC resistive control circuit UL 508 10 A 28 V DC resistive control circuit UL 508 |
| Maximum switching voltage | 300 V AC 30 V DC |
| Contact material | Silver alloy, gold flashed |
| Operating time | 20 ms - pick-up 20 ms - drop-out |
| Shape of pins | Spade |
| For use with | 8501NR43 |
| Height | 1.07 in (27.3 mm) |
| Width | 1.20 in (30.6 mm) |
| Depth | 1.65 in (41.8 mm) |

Environment

| | |
|---|---|
| Ambient temperature range - operational | -40...131 °F (-40...55 °C) |
| Product certifications | UL Listed[RETURN]UL Recognized[RETURN]CSA[RETURN]CE |

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | 21143-8501 R |
| Discount Schedule | CP2 |
| GTIN | 785901137122 |
| Returnability | Yes |
| Country of origin | CN |

Packing Units

| | |
|------------------------------|--------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.30 in (3.302 cm) |
| Package 1 Width | 1.70 in (4.318 cm) |
| Package 1 Length | 1.90 in (4.826 cm) |
| Package 1 Weight | 2.08 oz (58.967 g) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|