

Keywerks™ 1U Rack Mount Patch Panel

Keywerks™ 1U rack mount patch panel provides a flexible, high density termination solution for the telecommunications room and data center's horizontal distribution or equipment room. It is designed to accept all Keywerks jacks, Keywerks fiber optic adapters, and Keywerks audio/video connectors or any other product with standard Keystone footprint. The rear cable management bracket is included and helps to support cable bundles. The Keywerks 1U rack mount patch panel is compatible with standard 19 in. racks and cabinets.

Description

Features and Benefits

Applications

Certification and Compliance

Accepts all Keywerks modules or any other product with standard Keystone footprint

Rear cable management bracket included

Port numbering back & front and ID labels

Installation hardware and instruction manual included

Compatible with 19 inches racks and cabinets

Data center horizontal distribution

Telecommunications room

Data center equipment room

Consolidation point

Work area

TIA-569 Commercial Building Standard for Telecommunications Pathways and Spaces.

CEA/EIA-310 Cabinets, Racks, Panels and Associated Equipment standard.

ANSI/TIA-568-C.2 Balanced Twisted-Pair Telecommunications Cabling and Component Standards.

ANSI/TIA/EIA-606 Administration Standard for Telecommunications Infrastructure.

FCC part 68 Connection of the Terminal Equipment to the Telephone Network.

UL 94 Tests for Flammability of Plastic Material for Parts in Devices and Appliances.

cULus Bi-national (Canada, US) Listed Communication Circuit Accessories.

RoHS Directive on Restriction of Hazardous Substances.





WW000040 shown



WW000032 shown

Ordering Information

	Description	Part Number
	Keywerks 1U/24-port patch panel black, empty	WW000040
	Keywerks 1U/24-port patch panel loaded with CAT6A black modules	WW001500
	Keywerks 1U/24-port patch panel loaded with CAT6 black modules	WW000032
	Keywerks 1U/24-port patch panel loaded with CAT5e black modules	WW000022

Packaging

	Description
	Cardboard box, 1 unit per box.

Inclusion

1 rear cable management bracket kit, 12 nylon tie wraps,
4 Philips screws 10-32 & 4 Philips screws 12-24, 2 ID labels, instruction manual.

Physical Characteristics

	Parameter	Value
	Port capacity	24-port
	Plastic materials	UL 94V-0 ABS thermoplastic
	Panel material	Cold rolled steel (CRS) 0.060 in, ASTM 1008
	Finish	Black sandtext
	Weight	Loaded 1.95 kg (4.29 lbs) Empty 0.75 kg (1.65 lbs)
	Overall dimensions	482.59 mm (19 in) x 44.45 mm (1.75 in)

Mechanical Characteristics

	Parameter	Value
	Installation temperature	-20° C (-4° F) ~ 40° C (104° F)
	Storage temperature	-40° C (-40° F) ~ 125° C (257° F)