



Cable Testers

Pocket Continuity Tester for Coax Cable

- Simple compact wire tracing of coaxial cables
- Identifies and tests cable drops for pass, short faults and location via audible beep and LED indicators
- LED lights green on a correctly made cable drop, red for short fault
- Remote contains loud audible beep for easy location identification
- Replaceable AAA Alkaline battery, included
- Female to female F-adapter (included) enables testing of loose cables and installed cable runs
- Docked remote switches tester off to conserve battery life
- Pocket clip secures tester to shirt pocket



VDV512-007

Cat. No.	Location ID	Batteries	Included	Weight
NEW VDV512-007	1	1 x AAA	F-adapter, Pocket Clip, Battery	4.8 oz (136 g)

Coax Explorer™ 2 Testers

- Test coaxial cable and map up to 4 locations
- Simple push button operation
- Easy to read LED panel indicates PASS, OPEN or SHORT conditions, simplifying cable identification
- (2) Replaceable AAA Alkaline batteries, included
- Push-on remotes for ease of use
- Cat. No. VDV512-101 includes a removable holder with 4 color coded remotes to trace up to 4 locations at the same time



REMOTE REPLACEMENT KIT
VDV512-110



VDV512-100



VDV512-101



Cat. No.	Cable Type	Test-n-Map ID Remotes	Location ID	Batteries	Display	Included	Weight
VDV512-100	RG59, RG6/6Q, RG7, RG11	(1) Red Remote (included)	1	2 x AAA	LED	Batteries, Red Remote	3.0 oz (85g)
VDV512-101	RG59, RG6/6Q, RG7, RG11	4 (Included)	4	2 x AAA	LED	Batteries, 4 Colored Push-on Remotes, F-adapter, Snap-on Remote Holder	4.8 oz (136 g)

LAN Scout™ Jr. Tester

- Tests continuity on twisted pair data wiring (RJ45) connections
- Tone generator with 4 distinct tones
- Heavy-duty ports are designed for long life and repeated connections
- Large display with pin-to-pin wire map for easy identification
- Compact, contoured dual-material chassis fits comfortably in your hand
- Remote stores in tester



RJ45 Port



Self Storing Remote



VDV526-052



Features	VDV526-052
RJ45 8-wire Cables	•
Continuity Testing	•
Pass TIA-568A/B & Crossover/Uplink	•
LCD LCD Display	•
1 2 3 4 Wiremap	•
Open Fault	•
Short Fault	•
Miswire Fault	•
Split Pair Fault	•
Tones	4
Self-Storing Remote	•
Low Battery	•
Apo Auto Power Off	•
Voltage Warning	•
Shield Detection	•

Cat. No.	Cable Type	Test-n-Map ID Remotes	Location ID	Batteries	Display	Included	Weight
VDV526-052	CAT3, CAT5/5e, CAT6/6A	—	—	6V to 4 x LR44 Alkaline	LCD	Batteries	0.25 lb (0.11 kg)

See page 297 for additional information on warnings.



WARNING: Do NOT use on energized circuits or cabling systems.