



Main

Product	End tap box
Range	I-Line

Complementary

Rated Current	800 A aluminium
Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	29.14 in (740.16 mm)
Height	28 in (711.20 mm)
Width	11 in (279.40 mm)
Material	Aluminium busbar
I-LINE Value End	Bolt
Number of Phases	3 phase
For Use with	Busbar trunking 800 A aluminium
Protection Type	50 percent capacity integral ground bus
Wiring Configuration	4-wire

Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

Ordering and shipping details

Category	20002-AF2/AFH2 800A 4WIRE-COMM
Discount Schedule	PE8
GTIN	00785901815853
Package weight(Lbs)	130.00 lb(US) (58.967 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration

Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------