



Main

Range of Product	PowerLogic T300
Device short name	LV150

Complementary

Product or Component Type	Low voltage and transformer monitoring
Protection or fault passage indication function	ANSI 47 : negative sequence overvoltage ANSI 27 : undervoltage ANSI 59 : overvoltage ANSI 59N : neutral voltage displacement ANSI 37 : phase undercurrent
Power measurement	Active and reactive energy Power factor Current Voltage Frequency Active and reactive power Apparent energy Apparent power
Power quality analysis	Voltage sag and swell detection Voltage unbalance Individual harmonics Harmonic distortion Voltage magnitude
Measurement accuracy	Current class 0.5 Voltage class 0.5 Energy class 1 IEC 61557-12
Data recording	Sequence of event recording Sag and swell logs Counter Harmonics logs Event logs Demand values Min/Max of instantaneous values Current value before fault
Memory capacity	4 MB
Synchronisation time between inputs	1 ms
Control type	Illuminated push-button status:
Web services	Assistance in commissioning and operating the installation Alarm Reports and diagrams Security/Authority verification Operating/Status report Event log
[Us] rated supply voltage	12...48 V DC +/- 20 %
Power Consumption in VA	2 VA
Communication port protocol	IEC 60870-5-104
Communication port support	2 ETHERNET RJ45

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Number of inputs	8 digital IEC 61131-2 type 3
Measurement current	5 A 1 A
Analogue input type	Current 0.01...35 A (impedance 0.001 Ohm)4 x
Measurement voltage	: 0...30 V AC at 50/60 Hz (single or three phases)

Environment

Fixing mode	Clip-in DIN rail)
Type of installation	Indoor Outdoor in cabinet
Electromagnetic compatibility	Electrical fast transient/burst immunity test - test level: level 4 criteria A conforming to IEC 61000-4-4 Conducted RF disturbances - test level: level 3 criteria A conforming to IEC 61000-4-6 Conducted disturbance emission - test level: level 4 criteria A conforming to IEC 61000-4-16 100 kHz damped oscillating wave - test level: level 3 criteria A conforming to IEC 61000-4-12 Radiated radio-frequency electromagnetic field immunity test - test level: level 4 criteria A conforming to IEC 61000-4-3 Immunity to voltage dips criteria A conforming to IEC 61000-4-29 Electrostatic discharge - test level: level 4 criteria B conforming to IEC 61000-4-2 Surge immunity test - test level: level 3 criteria A conforming to IEC 61000-4-5 Magnetic field at power frequency - test level: level 5 criteria B conforming to IEC 61000-4-8 Conducted and radiated emissions class A conforming to EN 55022
IP degree of protection	Body IP2X IEC 60529 Front IP4X IEC 60529
IK degree of protection	IK07 IEC 62262
Relative humidity	5...95 % IEC 60068-2-30
Mechanical robustness	Vibrations 10...2000 Hz 1 gn 10 cycles IEC 60068-2-6 Bumps 10 gn 16 ms 1000 bumps non energized IEC 60068-2-29 Shocks 10 gn 11 ms 3 pulses in operation IEC 60068-2-27
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Ambient Air Temperature for Operation	-40...158 °F (-40...70 °C)
Operating altitude	9842.52 ft (3000 m)
Product Certifications	CE
Standards	IEC 60255-27 IEC 61557-12 IEC 62586-1 IEC 61000-4-30:class S IEC 61850
Height	5.51 in (140 mm)
Width	1.77 in (45 mm)
Depth	5.51 in (140 mm)
Net Weight	1.01 lb(US) (0.46 kg)

Ordering and shipping details

Category	08642-SAGE FEEDER RTU
Discount Schedule	RTU1
GTIN	3606480802997
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.99 in (7.6 cm)
Package 1 Width	7.52 in (19.1 cm)
Package 1 Length	7.80 in (19.8 cm)
Package 1 Weight	21.16 oz (600.0 g)
Unit Type of Package 2	S03

Number of Units in Package 2	8
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	10.58 lb(US) (4.8 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.