



## Cutting Oil Thread Cutting Lubricant, 340 Grams

No. 73500 | Item# 1006208 | Case# 1006207

Product Description	Cutting Oil is a superior thread cutting lubricant for use on all types of metals, including brass, copper and aluminum.
Applications	Tapping, threading, drilling, sawing, shearing, turning, and reaming metal parts, pipes, conduit, screws, bolt holes, housings, aluminum sheets, strapping, gears and chains.
Unit Package Description	16 Ounce (473 ml) Aerosol
Brand	CRC
Generic Description 1	Thread Cutting Lubricant
Net Fill	340 Grams
UPC Code	078254735009
Unit Dimensions	19.69H x 6.68W x 6.68D cm
Units Per Case	12
Case Dimensions	20.57H x 21.08W x 28.19D cm
Cases Per Pallet	133
Case Weight	5.44 kg
I 2 of 5 Code	30078254735000
Appearance	Brown Liquid
Base Type	Petroleum
Flash point (F)	>300°F
Flash point (C)	>148.9°C
Flammability Class - CPSC	Flammable
Spec Gravity Concentrate	0.9244
Plastic Safe	Safe on Acrylic Plastics
Film Type	Non-Drying
Working Temp (F)	Max 300°F
Working Temp (C)	Max 148.9°C
Propellant	Hydrocarbon
NSF Category Code	P1

Last revised: 3/8/2019

Page 1 of 2



CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



NSF Number	154095
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
Restricted from Sale In:	Not for sale in United States.
Removal (How To)	Remove with general purpose degreaser.