

# GAR2229TN, Mechanical Grounding Connector, Cable to Rod or Pipe, Tin Plated

By Burndy  
Catalog # [GAR2229TN](#)



Mechanical Grounding Connector, Cable to Rod or Pipe, 2/0 AWG (Sol) -250 kcmil, 4" Pipe, 4"-4-1/2" Rod, Tin Plated.

## Features

- Parallel or 90° Copper Cable Connection
- One-wrench installation
- Rated for Direct Burial in earth or concrete

## General

Catalog Number	GAR2229TN
Installation Torque	240 LBS/in
Recommended in-lb	
Plating Type	Tin - Hot Dipped
U Bolt Type	261
UPC	621945449398

## Dimensions

Dimension - B Length inch	4.50 in
Dimension - Height inch	6.38 in
Dimension - Height mm	162.1 mm
Dimension - L Length Overall mm	46 mm
Dimension - Length Overall inch	1.81 in
Dimension - Outside Diameter inch	4.50 in
Dimension - Width inch	5.82 in
Dimension - Width mm	148 mm

## Conductor Related

Conductor - Copper Solid Size	2/0;3/0;4/0
Conductor - Copper Solid Size Range	2/0 AWG-250 Kcmil

Conductor - Copper Str Size	1/0;2/0;3/0;4/0;250
Conductor - Copper Str Size Range	1/0 AWG - 250 kcmil
Conductor - Copper Tube Std Size	4;4 1/2
Conductor - Copper Tube Std Size Range	4-4 1/2
Conductor - Pipe or Round Tube Size	4 in
Conductor - Rod Size	4.0 - 4.5 in

## Certifications And Compliance

Buy American Compliant	Contact Manufacturer
Certification - CSA Approved	No
Certification - UL Listed Direct Burial	Yes
Standards - RoHS Compliance Status	EX
UL Listed	Yes

## Logistics

Minimum Pack Quantity	1
-----------------------	---

## Product Assets

- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR\\_GAR\\_Lineart](#)
- [Sales Drawings - SD..015789-01](#)