



### Main

|                           |                  |
|---------------------------|------------------|
| Product or Component Type | Plug-in unit     |
| Range of Product          | I-Line           |
| Circuit breaker type      | H-frame          |
| Trip unit technology      | Thermal-magnetic |

### Complementary

|   |   |
|---|---|
| Protection Type                                     | Circuit breaker   |
| Mounting Mode                                       | Plug-in   |
| [Ue] rated operational voltage                      | 600 V AC  |
| Line Rated Current                                  | 15 A  |
| Number of Phases                                    | 3 phase   |
| Poles description                                   | 3P  |
| Interrupt Rating                                    | 125 KA 240 V AC<br>100 KA 480 V AC<br>50 kA 600 V AC            |
| [Ics] rated service short-circuit breaking capacity | 80 %  |
| Wiring configuration                                | 4-wire (integral ground bus)                                    |
| AWG gauge   | AWG 8...AWG 3/0 1 phase and neutral<br>AWG 6...AWG 2/0 1 ground |
| Depth   | 9.13 in (232 mm)  |
| Height  | 8.50 in (216 mm)  |
| Width   | 21.69 in (551 mm)   |

### Environment

|                         |  |
|-------------------------|--|
| Product Certifications  | UL listed file E22182[RETURN]CSA C22.2 No 27 |
| Standards               | IEC 60529<br>UL 857                          |
| IP Degree of Protection | IP54   |

### Ordering and shipping details

|                   |                           |
|-------------------|---------------------------|
| Category          | 20182-PFA / PHD C/B PLUGS |
| Discount Schedule | PE7                       |
| Returnability     | No                        |

### Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Number of Units in Package 1 | 1                        |
| Package 1 Weight             | 32.00 lb(US) (14.515 kg) |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|