



## Main

Range Compatibility	PacDrive 3
Product or Component Type	Servo motor
Device short name	SH3.....P

## Complementary

Maximum mechanical speed	3800 rpm
[Us] rated supply voltage	115...480 V
Phase	Three phase
Continuous stall current	33.2 A
Continuous stall torque	835.51 lbf.in (94.4 N.m) 115...480 V three phase
Continuous power	10600 W
Peak stall torque	2920.74 lbf.in (330 N.m) 115...480 V three phase
Nominal output power	4450 W 115 V single phase 7790 W 230 V single phase 10620 W 400 V three phase 10100 W 480 V three phase
Nominal torque	751.43 Lbf.In (84.9 N.m) 115 V single phase 658.49 Lbf.In (74.4 N.m) 230 V single phase 448.73 Lbf.In (50.7 N.m) 400 V three phase 355.80 lbf.in (40.2 N.m) 480 V three phase
Nominal speed	500 rpm 115 V single phase 1000 rpm 230 V single phase 2000 rpm 400 V three phase 2400 rpm 480 V three phase
Maximum current Irms	136.1 A
Shaft end	Smooth shaft
Shaft diameter	1.50 in (38 mm)
Shaft length	3.15 in (80 mm)
IP degree of protection	Shaft bushing without shaft seal ring IP54 EN/IEC 60034-5 Motor IP65 EN/IEC 60034-5 Shaft bushing IP65 EN/IEC 60034-5
Encoder type	Absolute multiturn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	Without
Mounting Support	International standard flange
Motor flange size	8.07 in (205 mm)
Electrical Connection	Straight connector
Torque constant	2.76 N.m/A 248 °F (120 °C)
Back emf constant	172 V/krpm 68 °F (20 °C)
Number of motor poles	5
Rotor inertia	190 kg.cm <sup>2</sup>

Stator resistance	0.2 Ohm
Stator inductance	6.3 mH
Maximum radial force Fr	4500 N 1000 rpm 3570 N 2000 rpm 3120 N 3000 rpm
Maximum axial force Fa	740 N
Type of cooling	Natural convection
Length	19.25 in (489 mm)
Centring collar diameter	7.09 in (180 mm)
Centring collar depth	0.16 in (4 mm)
Number of mounting holes	4
Mounting holes diameter	0.55 in (14 mm)
Circle diameter of the mounting holes	8.46 in (215 mm)
Net Weight	147.71 lb(US) (67 kg)

## Ordering and shipping details

Category	18359-PACDRIVE3 SERVO MOTORS
Discount Schedule	PC52
GTIN	3606485298658
Returnability	No
Country of origin	DE

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.14 in (41.0 cm)
Package 1 Width	12.20 in (31.0 cm)
Package 1 Length	28.35 in (72.0 cm)
Package 1 Weight	156.75 lb(US) (71.1 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------