

Main

Actuator Type	Diaphragm
Application	Controlling small electrically driven air compressors
Approvals	UL Listed File: E12158 CCN NKPZ - CSA Certified File: LR25490 Class 3211 06
Contact Arrangement	DPST
Contact Rating	A600
Depth	2.78 Inches
Diaphragm	Nitrile (Buna N)
Differential	30 PSIG
Differential Type	Fixed
Enclosure Rating	NEMA 1
Enclosure Type	General Purpose (Indoor)
Height	2.80 Inches
Horsepower Rating (1-Phase)	1.5HP@115VAC - 2HP@230VAC
Horsepower Rating (3-Phase)	2HP@115VAC - 3HP@230VAC - 1HP@460/575VAC
Includes	Two-Way pressure release valve
Marketing Trade Name	Pumptrol
Maximum Allowable Pressure	220 PSIG
Maximum Voltage Rating	575VAC
Mounting Type	Bracket
Number of Poles	2-Pole
Pressure Connection	0.25 Inch NPSF
Pressure Setting	Off at 125 PSIG
Range on Increasing Pressure	70 to 150 PSIG
Terminal Type	Screw Clamp
Type	FHG
Weight	1.13 Pounds
Width	3.76 Inches

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.