



Product Family
Miller Permanent Anchorage Connectors

Anchorage Connectors are designed as the intermediary for securing a connecting device to an anchorage. The anchorage should be easily accessible, located at a safe distance and support 5,000 lbs. per worker

[Visit MillerFallProtection.com >](http://MillerFallProtection.com)
[Interactive Miller Catalog >](#)
[Access the Miller Photo Gallery >](#)



Product Numbers & Ordering Information

Product Numbers	Details
410/	Mounted D-Ring with Hardware Steel D-Ring with Plate; Complete with four 3/8-inch bolts, lockwashers, nuts, and drilling template.
415/	D-Bolt Anchor D-Bolt Anchor for up to 3/4-in. working thickness; Includes a 1/2-in. diameter bolt w/lockwasher and nut
416/	D-Bolt Anchor D-Bolt Anchor for up to 4-in. working thickness; Includes a 5/8-in. diameter bolt with lockwasher and nut
416SS/	D-Bolt Anchor Stainless Steel D-Bolt Anchor for up to 4-in. working thickness; Includes a 5/8-in. diameter bolt with lockwasher and nut
417/	D-Bolt Anchor D-bolt anchor without hardware (Note: User supplies mounting hardware – 5/8" grade 8 bolt, lockwasher and nut.)
417SS/	D-Bolt Anchor Stainless Steel D-bolt anchor without hardware (Note: User supplies mounting hardware – 5/8" grade 8 bolt, lockwasher and nut.)



418/

D-Bolt Anchor
3/4-Inch D-Bolt Anchor with Hardware



419/

D-Bolt Anchor
3/4-Inch D-Bolt Anchorage Connector

Overview

Key Features

Miller offers a variety of permanent anchorage connectors. Careful consideration should be given to selecting a proper anchorage for ultimate safety.

Recommended Industries/Use

- Construction

Hazards

- Confined Space
- Fall from height

Regulations

- - Meets all applicable OSHA, ANSI and CSA standards

Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

Specifications

Maximum Working Capacity

- 400 lbs. (181.4kg)

Literature & Documents

I298 D-Ring and D-Bolt Anchors Manual - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Permanent_Anchorage_Systems/42994/1033.aspx

I298 D-Ring and D-Bolt Anchors Product Instruction Manual

SP421 - 415-417 D-Bolt Spec Sheet - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Permanent_Anchorage_Systems/42995/1033.aspx

SP421 - 415, 415 and 417 D-Bolt Specification Sheet

SP422 - 410 Mounted D-ring Spec Sheet - US

http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Permanent_Anchorage_Systems/42996/1033.aspx

SP422 - 410 Mounted D-ring Specification Sheet

Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

Additional Information

800/873-5242 or 814/423-2118 email: millertechexpert@sperian.com

Technical Support

Contact Miller Technical Service at 800/873-5242 or 814/423-2118 email: millertechexpert@sperian.com