



### Main

Range	TeSys
Product or Component Type	Contactor coil
Device short name	LX1FG
Range compatibility	TeSys TeSys F LC1F contactor
Product Compatibility	LC1F225 LC1F185
Control circuit type	AC 50 Hz
[Uc] control circuit voltage	24 V AC 50 Hz
Inductance of closed circuit	0.03 H
Average resistance	0.18 Ohm 68 °F (20 °C)
Operating time	20...35 ms closing 7...15 ms opening
Mechanical durability	10 Mcycles
Maximum operating rate	2400 cyc/h 131 °F (55 °C)

### Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out 0.35...0.55 Uc 50/60 Hz 131 °F (55 °C) Operational 0.85...1.1 Uc 50/60 Hz 131 °F (55 °C)
Inrush power in VA	805 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Hold-in power consumption in VA	55 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat dissipation	18...24 W 50 Hz

### Environment

Ambient Air Temperature for Operation	23...131 °F (-5...55 °C)
Net Weight	1.21 lb(US) (0.55 kg)

### Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	3389110083200
Returnability	No

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.76 in (7.0 cm)
Package 1 Width	3.15 in (8.0 cm)
Package 1 Length	6.30 in (16.0 cm)
Package 1 Weight	18.77 oz (532.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)

Package 2 Length	15.75 in (40 cm)
Package 2 Weight	22.68 lb(US) (10.289 kg)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

### Contractual warranty

Warranty	18 months
----------	-----------