



## Main

Range of Product	Homeline
Product or Component Type	Load Center
Line Rated Current	225 A
[Ue] rated operational voltage	120/240 V AC
Mounting Mode	Wall mount
Short-circuit current	10 kA

## Complementary

Electrical Connection	Lugs
AWG gauge	AWG 6...250 kcmil aluminium/copper
Load center type	Main lugs
Number of spaces	30
Number of circuits	60
Number of tandem circuit breakers	30
Phase	1 phase
Cover type	Combination flush/surface cover
Device Composition	Grounding bar included (not installed)
Wiring configuration	3-wire
Material	Tin plated aluminium: busbar
Enclosure Material	Welded sheet steel
Cover colour	White
Box number	10

## Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 1 indoor)
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)

## Ordering and shipping details

Category	00199-DE5 MISC. SERVICE PARTS
Discount Schedule	DE5
GTIN	785901830757
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.60 in (14.224 cm)
Package 1 Width	16.40 in (41.656 cm)
Package 1 Length	36.70 in (93.218 cm)
Package 1 Weight	30.76 lb(US) (13.953 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations