



Main

| | |
|----------------------|------------------------|
| Marketing Trade Name | QO |
| Product Type | Load Center |
| Enclosure Type | Weatherproof enclosure |
| Cover Type | Surface cover |

Complementary

| | |
|--|---|
| PoN Convertible Mains (lugs) | Main breaker |
| Rated Current | 125 A |
| Number of Spaces | 30 |
| Max Short Circuit Current Rating | 25 kA |
| Maximum Number of Single Pole Circuits | 30 |
| Maximum Number of Tandem Breakers | 0 |
| Number of Phases | 3 phase |
| Voltage Rating | 208Y/120 V AC 240/120 V delta AC 240 V delta AC |
| Wire Size | AWG 4...300 kcmil aluminium/copper |
| Ground Bar | Grounding bar (ordered separately) |
| Electrical Connection | Lugs |
| Wiring Configuration | 3-wire 4-wire |
| Busbar Material | Tin plated copper: busbar |
| Enclosure Material | Welded galvanized steel |
| Surface Finish | Baked enamel Gray |
| Box Number | 14R |
| Height | 39.37 in (1000 mm) |
| Width | 14.76 in (375 mm) |

Environment

| | |
|---------------------------------------|---------------------------------|
| Enclosure Rating | NEMA 3R outdoor |
| Ambient Air Temperature for Operation | 23 °F (-5 °C) 104 °F (40 °C) |
| Product Certifications | UL Listed |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

| | |
|-------------------|----------------------------------|
| Category | 00017-QO 3PH LOAD CENTER,OUTDOOR |
| Discount Schedule | DE3 |
| GTIN | 785901290599 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.00 in (12.7 cm) |
| Package 1 Width | 15.31 in (38.9 cm) |
| Package 1 Length | 41.10 in (104.4 cm) |
| Package 1 Weight | 45.90 lb(US) (20.82 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|