

Product Datasheet

Characteristic

XZCP1141L15

pre-wired connectors XZ - straight
female - M12 - 4 pins - cable PUR 15m



Main

accessory / separate part category	Cabling accessory
accessory / separate part type	Pre-wired connectors
series name	General purpose

Complementary

electrical connection	M12, 4 pins straight female connector
cable connector fixing	Screw-on
collar material	Metal
status LED	Without
cable length	49.21 ft (15 m)
cable outer diameter	0.2 in (5.2 mm)
cable composition	4 x 0.34 mm ²
wire insulation material	PUR
System Voltage	250 V AC 300 V DC
Line Rated Current	4 A
contact resistance	5000 µOhm
insulating resistance	1 GΩ
product weight	1.15 lb(US) (0.52 kg)

Environment

IP degree of protection	IP65 IP67 IP69K
product certifications	cULus
ambient air temperature for operation	-40...176 °F (-40...80 °C) (static) 23...176 °F (-5...80 °C) (flexing)
ambient air temperature for storage	-40...176 °F (-40...80 °C)

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

RoHS (date code: YYWW)	Compliant - since 0649 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available