



## Main

Range of product	Modicon Quantum automation platform
Product or component type	Analogue input module
Analogue input number	8
Analogue input resolution	12 bits
Type of filter	Single pole low pass - 3 dB at 15 Hz +/- 20 %

## Complementary

Input type	Differential
Addressing requirement	9 input words
Linear measuring range	1...5 V 4...20 mA
Absolute maximum input	25 mA 50 V DC
Input impedance	250 MOhm current +/- 0.03 % > 20 Ohm voltage
Absolute accuracy error	+/- 0.05 % of full scale +/- 0.1 % of full scale maximum
Linearity error	+/- 0.04 %
Accuracy drift according to temperature	+/- 0.0025 % of full scale/°C <= 0.005 % of full scale/°C
Common mode rejection	> -72 dB 60 Hz
Isolation between channels and bus	1000 V DC 3000 V DC 60 s
Isolation between channels	30 V DC
Update time	5 ms
Fault type	Broken wire 4...20 mA Undervoltage range 1...5 V
Marking	CE
Local signalling	1 LED green bus communication is present (Active) 1 LED red external fault 8 LEDs green channel is turned on 8 LEDs red channel fault
Bus current requirement	240 mA
Power dissipation in W	2 W
Module format	Standard
Product weight	0,3 kg

## Environment

Standards	CSA 22-2 No 142 UL 508
Product certifications	FM Class 1 Division 2 CUL
Resistance to electrostatic discharge	4 kV contact IEC 801-2 8 kV on air IEC 801-2
Resistance to electromagnetic fields	10 V/m 80...1000 MHz IEC 801-3

Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % without condensation
Operating altitude	≤ 5000 m
RoHS EUR conformity date	0852
RoHS EUR status	Compliant