

WQB B/10**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image**General ordering data**

| | |
|------------|---|
| Version | Cross-connector (terminal), when screwed in, black, 24 A, Number of poles: 10, Pitch in mm (P): 5.10, Insulated: Yes, Width: 48.26 mm |
| Order No. | 1579050000 |
| Type | WQB B/10 |
| GTIN (EAN) | 4008190094508 |
| Qty. | 20 pc(s). |

Creation date November 26, 2024 12:16:46 PM CET

Catalogue status 26.11.2024 / We reserve the right to make technical changes.

WQB B/10

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|----------|-----------------|------------|
| Depth | 2.5 mm | Depth (inches) | 0.098 inch |
| Height | 23.5 mm | Height (inches) | 0.925 inch |
| Width | 48.26 mm | Width (inches) | 1.9 inch |
| Net weight | 3.33 g | | |

Temperatures

| | | | |
|---------------------|----------------|----------------------------------|-------|
| Storage temperature | -25 °C...55 °C | Continuous operating temp., max. | 70 °C |
|---------------------|----------------|----------------------------------|-------|

Material data

| | | | |
|----------|---------------|--------|-------|
| Material | tinned copper | Colour | black |
|----------|---------------|--------|-------|

System specifications

| | |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

Additional technical data

| | | | |
|--------------------------|-----------------|---------------------|-----------------|
| Explosion-tested version | No | Installation advice | Direct mounting |
| Type of fixing | when screwed in | | |

Cross-connector

| | | | |
|-------------------------------------|-----------------|---------------------------|------|
| Number of cross-connected terminals | 10 | Rated current, multi-pole | 24 A |
| Type | Cross-connector | | |

Dimensions

| | | | |
|-----------------|--------|--------------|-------|
| Pitch in mm (P) | 5.1 mm | TS 35 offset | 54 mm |
|-----------------|--------|--------------|-------|

General

| | | | |
|---------------------|-----------------|-----------------|----|
| Installation advice | Direct mounting | Number of poles | 10 |
|---------------------|-----------------|-----------------|----|

Rating data

| | | | |
|---------------|-------|---------------|------|
| Rated voltage | 800 V | Rated current | 24 A |
|---------------|-------|---------------|------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000489 | ETIM 7.0 | EC000489 |
| ETIM 8.0 | EC000489 | ETIM 9.0 | EC000489 |
| ECLASS 9.0 | 27-14-11-40 | ECLASS 9.1 | 27-14-11-40 |
| ECLASS 10.0 | 27-14-11-40 | ECLASS 11.0 | 27-14-11-40 |
| ECLASS 12.0 | 27-14-11-40 | ECLASS 13.0 | 27-25-03-03 |
| ECLASS 14.0 | 27-25-03-03 | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Creation date November 26, 2024 12:16:46 PM CET

Catalogue status 26.11.2024 / We reserve the right to make technical changes.

Data sheet**WQB B/10**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data**Approvals**

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|--------------------|--|
| Engineering Data | CAD data – 18599_WQB_B-10_DXF.dxf CAD data – STEP |
| User Documentation | StorageConditionsTerminalBlocks |
| Catalogues | Catalogues in PDF-format |