


H22R Series



2 POSITION - 200 AMP / POSITION 200 Amp Mains

CATALOGUE #	DESCRIPTION	METER POSITIONS	ENCLOSURE SIZE A X B X C	WEIGHT
H22R	2 gang, 200 Amp main, 200 per position	2	15 ¹ / ₈ " x 5 ³ / ₈ " x 17 ³ / ₄ "	42 lbs.
H23R	3 gang, 200 Amp main, 200 per position	3	15 ¹ / ₈ " x 5 ³ / ₈ " x 26 ¹ / ₂ "	58 lbs.
H24R	4 gang, 200 Amp main, 200 per position	4	15 ¹ / ₈ " x 5 ³ / ₈ " x 35 ¹ / ₄ "	74 lbs.

- Factory Bussed - 200 Amp Mains
- 4 Jaw meter socket
- 200 Amp - 600 Volts per position
- CSA enclosure 3
- Approved conductor range:
Line 6-250 MCM AWG CU/AL
Load No. 6-250 MCM AWG
- Combination OH/UG

- Order "SXC" hubs separate
- Approved for overhead or underground use

KNOCKOUT CODE	CONDUIT SIZE
G	1 ¹ / ₄ ", 1 ¹ / ₂ ", 2", 2 ¹ / ₂ "
AA	1 ¹ / ₂ "
F	1 ¹ / ₄ ", 1 ¹ / ₂ ", 2", 2 ¹ / ₂ ", 3"

