



Main

Product or Component Type	Single Throw Safety Switch
Series name	General duty

Complementary

Device Composition	Neutral (factory installed)
Disconnect device type	Fusible disconnect
Short-circuit current	100 kA maximum cartridge
Device mounting	Surface
Number of poles	3
Electrical Connection	Lugs
[Ue] rated operational voltage	120/240 V AC
Motor power hp	75 Hp at 240 V AC 50-60 Hz for 3 phase motors 150 hp at 240 V AC 50-60 Hz for 3 phase motors
AWG gauge	AWG 3/0...500 kcmil copper or aluminium
Tightening torque	450 lbf.in (50.84 N.m) (AWG 4...500 kcmil)
Height	49.13 in (1247.90 mm)
Width	25.13 in (638.30 mm)
Depth	8.88 in (225.55 mm)

Environment

Product Certifications	CSA
NEMA degree of protection	NEMA 3R galvanized steel

Ordering and shipping details

Category	00008-H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE 1
GTIN	785901204787
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	49.13 in (124.8 cm)
Package 1 Width	25.12 in (63.8 cm)
Package 1 Length	8.90 in (22.6 cm)
Package 1 Weight	135.00 lb(US) (61.235 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------