

**CENTRAL VACUUM HOSES
MODELS BN32DV, BN32LV & BN32**

**MODEL BN32DV
DUAL-VOLTAGE CRUSHPROOF HOSE**



- 32' (9.8 m) length: 2' (0.7 m) longer than industry standard
- 1½" (35 mm) diameter crushproof hose
- Full 360° handle rotation
- Three-positions intake air control valve to adjust suction power
- Three-position switch for complete control of both the vacuum and power brush in your hand
- Universal nozzle designed to fit most wall outlets
- Hose hanger for fast and easy storage included
- UL Recognized 

**MODEL BN32LV
LOW-VOLTAGE CRUSHPROOF HOSE**



- 32' (9.8 m) length: 2' (0.7 m) longer than industry standard
- 1½" (35 mm) diameter crushproof hose
- Full 360° handle rotation
- Three-positions intake air control valve to adjust suction power
- Two-position switch for complete control of the vacuum in your hand
- Universal nozzle designed to fit most wall outlets
- Hose hanger for fast and easy storage included

**MODEL BN32
STANDARD HOSE**



- 32' (9.8 m) length: 2' (0.7 m) longer than industry standard
- 1¼" (32 mm) diameter crushproof hose
- Intake air control valve to adjust suction power
- Universal nozzle designed to fit most wall outlets
- Hose hanger for fast and easy storage included

Broan-NuTone Canada; Mississauga, Ontario www.broan.ca 877-896-1119

REFERENCE	QTY.	REMARKS	Project	
			Location	
			Architect	
			Engineer	
			Contractor	
			Submitted by	Date