



GE
Lighting

22622 - GE LED HID - Type B

LED115ED28/740

- ☞ Open and Closed Rated
- ☞ Ballast Bypass required
- ☞ Damp
- ☞ DLC Rated
- ☞ Not suitable for air-tight explosive or hazardous fixtures
- ☞ For additional collateral click the link below: https://products.currentbyge.com/led-lamps-and-modules/led-replacement-for-hid

Product Photo



GENERAL CHARACTERISTICS

| | |
|--------------------------------|---------------------|
| Base Description | EX39 Screw |
| Base Type | Screw-In |
| Body Color | Clear |
| Dimmable | No |
| Primary Application | Replacement for HID |
| Product Color | Clear |
| Product Technology | LED |
| Rated Life (Hours) | 50000 h |
| Dimmable / Non-Dimmable | No |
| Lamp Count | 1 |
| Life in Years | 17.1 yr |
| Replacement Watts | 400 W |
| Requested Structure | Carton |
| Estimated Energy Cost per Year | 36.94 |

PHOTOMETRIC CHARACTERISTICS

| | |
|------------------------|----------|
| Rated Beam Spread | 115 W |
| Initial Lumens-nominal | 16000 lm |
| Color Temperature | 4000 K |

PRODUCT INFORMATION

| | |
|----------------------------------|----------------|
| Product Code | 22622 |
| Description | LED115ED28/740 |
| Alternative Unit Of Measure | EACH |
| Standard Package Quantity | 3 |
| Ean UPC | 043168226226 |
| Standard Package GTIN | 00043168226226 |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 3 |
| Sales Unit | Each |
| UCC | |
| Alternative Unit Of Measure | CASE |
| Standard Package Quantity | 3 |
| Ean UPC | 043168226226 |
| Standard Package GTIN | 10043168226223 |
| No Of Items Per Sales Unit | |
| No Of Items Per Standard Package | 3 |
| Sales Unit | Case |
| UCC | |

DIMENSIONS

| | |
|-----------------------------|--------|
| Bulb Max Overall Length-MOL | 8.3 in |
|-----------------------------|--------|

ELECTRICAL CHARACTERISTICS

| | |
|---------------------|-------|
| Voltage <Nom> | 120 V |
| Rated power (Watts) | 115 W |