



5" Angle Grinder

Model No:GA5020C

"SJS" Technology, Electronic Current Limiter, Soft Start, Constant Speed Control

Trigger Switch With Lock-On Button (AC)

- SJS (Super Joint System) prevents kickback during wheel lock up for optimal tool and operator protection
- Electronic current limiter prevents motor burnout due to overloading
- Soft start feature gradually increases speed to eliminate start up shock
- Constant speed control maintains constant speed under heavy load
- Anti-Restart feature prevents accidental start up of tool if switch is locked in the on position
- LED Light indicates active power supply and activation of anti-restart feature
- Labyrinth construction features a complex series of channels to prevent penetration of dust and debris into the field and armature for maximum operational life
- Motor winding protection features "Zig-Zag" varnish on the armature and hardened powder on the field coils to act as an impenetrable barrier to dust and debris
- Rotatable gear housing can be positioned at every 90° for optimal positioning
- Removable side handle can be mounted on left or right side of tool
- Ergonomic soft rubber grip design for vibration absorption and comfortable operation



STANDARD EQUIPMENT

INCLUDES:

Anti-Vibration Side Handle (194514-0), Lock Nut Wrench 28 (782424-9), Toolless Wheel Cover(123145-8), 5" Depressed Centre Wheel (1 Ea. A-95962-25), Inner Flange 45(224399-1), Lock Nut 5/8-45(224568-4)

SPECIFICATIONS

Maximum Capacities:

Grinding/Sanding --5" (125 mm)

Sanding Disc --5" (125 mm)

Wire Cup Brush --3-1/2" (90 mm)

Spindle Thread --5/8" - 11 UNC

No Load Speed: --11,000 RPM

AMPS (120V) --12.5 A

Vibration Level --9.5 m/s²

Noise Level --90 dB(A)

Overall Length --15-3/8" (390 mm)

Net Weight --6.4 lbs (2.9 kg)

Note: Makita Canada reserves the right to change specification of products without notice. The contents of the parts breakdown and Instruction manuals may be different from current products.