

Product data sheet

Characteristics

EE15S3534H

Transformer, dry type, DOE 2016, 15kVA, 1 phase, 600V primary, 120/240V secondary, 17D, 150C rise



Main

| | |
|------------------------|------------------------------|
| Product | Energy Efficient Transformer |
| Enclosure Code | 17D |
| Enclosure Type | NEMA 2 |
| Insulation Temperature | 428 °F (220 °C) |
| Phase | 1 phase |
| Primary Voltage | 600 V |
| Power Rating | 15 kVA |
| Secondary Voltage | 120/240 V |
| Full Capacity Taps | 6 2.5 % 2+ 4- |
| Temperature Rise | 150 °C |
| Winding Material | Aluminium |

Ordering and shipping details

| | |
|-------------------|-----------------------------|
| Category | 16284-1 PH EE/TP1 LVGP XFMR |
| Discount Schedule | PE2E |
| GTIN | 785901688402 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|---------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 33.10 in (84.074 cm) |
| Package 1 Width | 21.80 in (55.372 cm) |
| Package 1 Length | 17.80 in (45.212 cm) |
| Package 1 Weight | 216.05 lb(US) (97.997 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| RECh Regulation | RECh Declaration |
| RECh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Approximate Dimensions

