


Date: _____
 In hands date of project: _____
 Project name/Number: _____
 Name of distributor: _____
 Client #: _____
 Name of end user: _____



Nominal length : 46 in. (1 168 mm) Dia. : 5/8 in. (16 mm)

ORDERING INFORMATION

Order code: 65481
 Description: LED/T5/S2/25.5W/850/46/STD/SMX
 UPC: 69549654815
 Case quantity: 25



PERFORMANCE DATA

Shape: T5
 Base: G5
 Watts (W): 25.5
 Starting method: Program Start
 Lamp voltage (VAC): 120 V-277 V / 347 V
 Color temperature (K)**: 5 000
 Average life (L70 hours): 50 000
 Initial Lumens (lm)*: 3 476
 Initial lumens per watt (lm/W): 136
 CRI: >80
 Beam angle (°): >240
 Coating: PET Polyethylene Terephthalate
 Operating temperature range: -20°C / -4°F to 45°C / 113°F
 DLC Listed: DLC Standard

*Initial lumens range: +/- 10 % **Typical colour temperature range: +/- 5 %



CAUTIONS

THIS LAMP OPERATES ON PROGRAM START ELECTRONIC BALLASTS. Direct replacement for 54 watts T5 lamps only. Risk of fire. Do not install this lamp in a pre-heat luminaire. Risk of electric shock – for use in damp locations. This device is not intended for use with emergency exit fixtures or emergency exit lights.

Qty	Description	Price

I accept the specifications of the lamp configuration mentioned above.

Name: _____
 Company: _____
 Signature: _____

Date: _____

Data is based upon tests performed in a controlled environment and representative of relative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice.

ORDERING INFORMATION

Order code: 65481
 Description: LED/T5/S2/25.5W/850/46/STD/SMX
 UPC: 69549654815
 Case quantity: 25

Ballast Compatibility List - 120-277 V (1/2)

Ballast Description			1 Lamp		2 Lamps		3 Lamps		4 Lamps	
Brand	Order Code	Number of lamps	Input Voltage							
			120 V	277 V	120 V	277 V	120 V	277 V	120 V	277 V
Advance	EL1/254A26	2								
	HCN-4S54-2LS-H	2								
	ICN-2S54	2								
	ICN-2S54-N	2								
	ICN-2S54-T	2								
	ICN-2S54-90C-N	2								
	IOP-2PSP54-SC	2								
	IZT-2S54-D	2								
	ICN-4S54-90C-2LS-G	4								
IOP-4PSP54-2LS-G	4									
Damar	26947A	2								
Espen	VE454MVHRP	4								
Fulham	RHA-UNV-254-LT5	2								
	RHA-UNV-454-LT5	4								
	WH5-120-L	2								
Fusion	FB254T5MVE	2								
	FB454T5MVE	4								
GE	GE254MVPS-D	2								
	GE254MVPS-D-1	2								
	GE254MVPS90-A	2								
	GE454MVPS90-F	4								
Halco	EP254HO/PS/MV/MC	2								
	EP454HO/PS/MV	4								
HEP	SI 254-58 UNI	2								
	SD 254-58 UNI	2								
Huafeng	ENP-T5-54-S2MC	2								
	ENP-T5-54-S4LC	4								
Keystone	KTEB-254HO-UV-PS/A	2								
	KTEB-254HO-UV-PS-SL	2								
	KTEB-454HO-UV-PS	4								
Liyuan	LYEB5812	2								
Luma	BLF254-U	2								
Maxlite	SKEU542HOP/SC	2								

■ compatible
 ■ non-compatible
 N/A

NOTE: STANDARD's ballast testing is limited to the above mentioned ballasts, however ballasts of the appropriate type that are manufactured in accordance to ANSI standards should be compatible with STANDARD LED fluorescent replacement lamps. Testing in each application is suggested. For complete ballast compatibility list visit www.standardpro.com.

ORDERING INFORMATION

Order code: 65481
 Description: LED/T5/S2/25.5W/850/46/STD/SMX
 UPC: 69549654815
 Case quantity: 25

Ballast Compatibility List - 120-277 V (2/2)

Ballast Description			1 Lamp		2 Lamps		3 Lamps		4 Lamps	
Brand	Order Code	Number of lamps	Input Voltage							
			120 V	277 V	120 V	277 V	120 V	277 V	120 V	277 V
Osram	QHE 2x54T5HO/UNV PSN	2								
	QT 2x54/120PHO-DIM	2								
	QTP 2x54T5HO/UNV PSN	2								
	QTP 2x54T5HO/UNV PSN HT	2								
	QTP 2x54T5HO/UNV PSN 80-SC	2								
	QHE 4x54T5HO/UNV PSN HT SCL	4								
	QHE 4x54T5HO/UNV PSN HT SCL[DOE]	4								
	QTP 4x54T5HO/UNV PSN HT W	4								
Pacific	EB-254PRS-U	2								
Roberson	PSB454T5MV	4								
Sunpark	U-2/54T5HO	2								
Symban	SLFE-254 T5HO-120MV-90C	2								
	SLFE-454 T5HO-120MV-90C	4								
Standard	57641 - E154T5PS120-277/N/HO	1								
	63025 - E245T5HOPS120-277/N/XTRM	2								
	63027 - E454T5HOPS120-277/N/XTRM	4								
Ultrasave	ER254120MHT-W	2								
Universal	B254PUNV-D	2								
	B254PUNVHB-D	2								
	B454PUNV-E	4								
	B454PUNVHB-E	4								

Ballast Compatibility List - 347 V

Ballast Description			1 Lamp		2 Lamps		3 Lamps		4 Lamps	
Brand	Order Code	Number of lamps	Input Voltage							
			347 V							
Advance	HCN-2S54-90C-WL	2								
	HCN-4S54-90C-2LS-G	4								
Fusion	FB232347E-HE	2								
Osram	QHE 2x54T5HO/347-480PSN HT	2								
	QHE 4x54T5HO/347-480PSN HT SCL	4								
Symban	SLFE-254 T5HO-347V-90C	2								
	SLFE-454 T5HO-347V-90C	2								
Standard	63026 - E254T5HOPS347/N/XTRM	2								
	63028 - E454T5HOPS347/N/XTRM	4								

■ compatible
 ■ non-compatible
 N/A

NOTE: STANDARD's ballast testing is limited to the above mentioned ballasts, however ballasts of the appropriate type that are manufactured in accordance to ANSI standards should be compatible with STANDARD LED fluorescent replacement lamps. Testing in each application is suggested. For complete ballast compatibility list visit www.standardpro.com.