



## Main

Product or component type	Starter
Range of product	Type S

## Complementary

Control circuit	Separate control circuit
Control type	Without
NEMA degree of protection	Not rated (open device)
Auxiliary contact composition	Without
Maximum Horse Power Rating	10 Hp 200 V AC, 3 phase 15 Hp 230 V AC, 3 phase 25 hp 460/575 V AC, 3 phase
Poles description	3P
Maximum operating voltage	600 V
NEMA size	2
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Local signalling	Without pilot light
Motor starter type	2 speed
Electrical connection	Lugs
Thermal overload type	Melting alloy
Number of thermal units required	6
Asynchronous motor control profile	Constant/variable torque
Maximum operating current	45 A

## Environment

Product certifications	UL listed file E78351 CCN NLDX CSA LR60905 class 3211 04
------------------------	---

## Ordering and shipping details

Category	21302 - 8810,11,12 S
Discount Schedule	CP1
GTIN	00785901497288
Nbr. of units in pkg.	1
Package weight(Lbs)	17.14 lb(US) (7.77 kg)
Returnability	No
Country of origin	MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------