

Product data sheet

Specifications



IEC contactor, TeSys D,
nonreversing, 80A resistive, 4 pole,
4 NO, 110VAC 50/60Hz coil, open
style

LC1D65004F7

**Product availability: Non-Stock - Not normally stocked in
distribution facility**

Main

Range of Product	TeSys Deca
Product or Component Type	Contactors
Device short name	LC1D
Contactors application	Resistive load
Utilisation category	AC-1 AC-3 AC-3e AC-4
Poles description	4P
[Ue] rated operational voltage	Power circuit <= 690 V AC 25...400 Hz
[Ie] rated operational current	80 A (at <140 °F (60 °C)) AC AC-1 for power circuit
[Uc] control circuit voltage	110 V AC 50/60 Hz

Complementary

Maximum Horse Power Rating	10 hp at 230/240 V AC 60 Hz for 1 phase motors conforming to CSA 10 hp at 230/240 V AC 60 Hz for 1 phase motors conforming to UL 20 hp at 200/208 V AC 60 Hz for 3 phase motors conforming to CSA 20 hp at 200/208 V AC 60 Hz for 3 phase motors conforming to UL 20 hp at 230/240 V AC 60 Hz for 3 phase motors conforming to CSA 20 hp at 230/240 V AC 60 Hz for 3 phase motors conforming to UL 5 hp at 115 V AC 60 Hz for 1 phase motors conforming to CSA 5 hp at 115 V AC 60 Hz for 1 phase motors conforming to UL 50 hp at 460/480 V AC 60 Hz for 3 phase motors conforming to CSA 50 hp at 460/480 V AC 60 Hz for 3 phase motors conforming to UL 50 hp at 575/600 V AC 60 Hz for 3 phase motors conforming to CSA 50 hp at 575/600 V AC 60 Hz for 3 phase motors conforming to UL
Compatibility code	LC1D
Pole contact composition	4 NO
Protective cover	With
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C)) for control circuit 80 A (at 140 °F (60 °C)) for power circuit
Irms rated making capacity	1000 A at 440 V for power circuit conforming to IEC 60947 140 A AC for control circuit conforming to IEC 60947-5-1
Rated breaking capacity	1000 A at 440 V for power circuit conforming to IEC 60947
Associated fuse rating	10 A gG for control circuit conforming to IEC 60947-5-1 125 A gG at <= 690 V coordination type 2 for power circuit 160 A gG at <= 690 V coordination type 1 for power circuit
Average impedance	1 mOhm - Ith 80 A 50 Hz for power circuit
Power dissipation per pole	6.4 W AC-1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Ui] rated insulation voltage	Control circuit 600 V CSA Control circuit 600 V UL Power circuit 600 V CSA Power circuit 600 V UL Control circuit 690 V IEC 60947-1 Power circuit 690 V IEC 60947-1
Overvoltage category	III
[Uimp] rated impulse withstand voltage	8 kV IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical durability	6 Mcycles
Control circuit type	AC 50/60 Hz standard
Coil technology	Without built-in bidirectional peak limiting diode suppressor
Control circuit voltage limits	0.3...0.6 Uc (140 °F (60 °C)):drop-out AC 50/60 Hz 0.8...1.1 Uc (140 °F (60 °C)):operational AC 50 Hz 0.85...1.1 Uc (140 °F (60 °C)):operational AC 60 Hz
Inrush power in VA	140 VA cos phi 0.75 (at 68 °F (20 °C)) 160 VA cos phi 0.75 (at 68 °F (20 °C))
Hold-in power consumption in VA	13 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 15 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat dissipation	4...5 W at 50/60 Hz for control circuit
Operating time	12...26 ms closing 4...19 ms opening
Maximum operating rate	3600 cyc/h at 60 °C
Connections - terminals	Control circuit: screw clamp terminals 1 0.002...0.006 in² (1...4 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.002...0.006 in² (1...4 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 0.002...0.006 in² (1...4 mm²) - cable stiffness: solid without cable end Power circuit: screw clamp terminals 1 0.002...0.05 in² (1...35 mm²) - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 0.002...0.04 in² (1...25 mm²) - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 0.002...0.05 in² (1...35 mm²) - cable stiffness: solid without cable end
Tightening torque	Control circuit 10.6 lbf.in (1.2 N.m) screw clamp terminal flat Ø 6 mm Control circuit 10.6 lbf.in (1.2 N.m) screw clamp terminal Philips No 2 Power circuit 44.3 lbf.in (5 N.m) screw clamp terminal flat Ø 6 mm Power circuit 44.3 lbf.in (5 N.m) screw clamp terminal flat Ø 8 mm Control circuit 10.6 lbf.in (1.2 N.m) screw clamp terminal pozidriv No 2
Auxiliary contacts type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts
Mounting Support	Rail Plate

Environment

Standards	IEC 60947-5-1 EN 60947-4-1 EN 60947-5-1 UL 60947-4-1 IEC 60947-4-1 CSA C22.2 No 14
Product Certifications	CCC BV DNV UL GL CSA LROS (Lloyds register of shipping) RINA GOST UKCA
IP degree of protection	IP2X IEC 60529 IP2X VDE 0106
Protective treatment	TH 3)IEC 60068
Permissible ambient air temperature around the device	23...140 °F (-5...60 °C) -40...158 °F (-40...70 °C) at Uc
Operating altitude	9842.52 ft (3000 m) without derating
Fire resistance	1562 °F (850 °C) IEC 60695-2-1
Flame retardance	V1 conforming to UL 94
Mechanical robustness	Shocks contactor open 8 Gn for 11 ms) Shocks contactor closed 10 Gn for 11 ms) Vibrations contactor opened 2 Gn, 5...300 Hz) Vibrations contactor closed 3 Gn, 5...300 Hz)
Height	5 in (127 mm)
Width	3.3 in (85 mm)
Depth	5.1 in (130 mm)
Product Weight	3.17 lb(US) (1.44 kg)

Ordering and shipping details

Category	US10I1222357
Discount Schedule	0I12
GTIN	3389110231762
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	6.0 in (15.2 cm)
Package 1 Width	5.2 in (13.2 cm)
Package 1 Length	4.3 in (10.8 cm)
Package weight(Lbs)	3.245 lb(US) (1.472 kg)
Unit Type of Package 2	S02
Number of Units in Package 2	5
Package 2 Height	5.9 in (15 cm)

Package 2 Width	11.8 in (30 cm)
Package 2 Length	15.7 in (40 cm)
Package 2 Weight	17.229 lb(US) (7.815 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	70 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	9 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.3 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	57 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	76
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Offer Marketing Illustration

Product benefits / Features

TeSys Deca Contactors



Reliable

Multi-standard solutions, high reliability, long mechanical and electrical durability for different sizes, and the most complete accessories.



Energy efficiency

These electronic-coil contactors require up to 80 % less energy than electro-mechanical contactors.



Universal

Multi standards certified (IEC, UL, CSA, CCC, EAC, Marine), Green Premium compliant (RoHS/REACH).



6

Schneider
Electric

Jun 27, 2026

Offer Marketing Illustration

Product benefits / Features



The image shows a TeSys Deca Contactor, a black industrial electrical component. It has a green label with 'TeSys' and 'Schneider Electric' logos. The label also indicates 'Control' and 'LC1 D09'. The top of the unit has three screw terminals labeled 'S-1', 'S-2', and 'S-3'. Below these are three more terminals labeled '13 NO', '22 NC', and 'A1'. The bottom of the unit has three screw terminals labeled '2T', '4T', and '6T'. The unit is shown against a green circular background.

TeSys Deca Contactors

Technical Benefits

- Deca green delivers a consistent low consumption range of contactors from 9 A to 80 A.
- Covers control voltage from 24 to 250 V, with same coils for AC and DC.
- Designed to meet the requirements of industrial and HVAC applications
- With IEC60335-1 compliance, improved fire resistance, and dust-proof auxiliaries
- Suitable for safety applications thanks to mechanically linked contacts and mirror contacts
- Outstanding breaking/making capacity up to 20 In with PLC direct connection

Offer Marketing Illustration

Product benefits / Features



TeSys Deca Contactors

Range Accessories



Auxiliary contact block



Time delay auxiliary contact block



Mechanical interlock



Comb busbar



Assembling kits



Power connections



Contactor Coil