



## Main

|                           |                     |
|---------------------------|---------------------|
| Range                     | TeSys<br>TeSys Deca |
| Product or Component Type | Shunt trip release  |
| Device short name         | GVAS                |

## Complementary

|                                 |  |
|---------------------------------|--|
| Range compatibility             | TeSys GV2ME<br>TeSys GV2LE<br>TeSys GV2L<br>TeSys GV2P<br>TeSys GV3L<br>TeSys GV3P<br>TeSys Deca   |
| [Uc] control circuit voltage    | 110...115 V AC 60 Hz   |
| Control circuit voltage limits  | 0.7...1.1 Un   |
| [Ui] rated insulation voltage   | 690 V AC IEC 60947-1<br>600 V AC UL 60947-4-1<br>600 V AC CSA C22.2 No 60947-4-1   |
| Threshold tripping voltage      | 0.75...0.2 Un  |
| Inrush power in VA              | 14 VA AC   |
| Inrush power in W               | 10.5 W   |
| Hold-in Power Consumption in VA | 5 VA AC  |
| Hold-in power consumption in W  | 1.6 W  |
| Operating time                  | 10...15 ms IEC 60947-1   |
| On-load factor                  | 100 %  |
| Connections - terminals         | Screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )solid<br>Screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )solid<br>Screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> )flexible without cable end<br>Screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> )flexible without cable end<br>Screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (0.75...1.5 mm <sup>2</sup> )flexible with cable end<br>Screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (0.75...1.5 mm <sup>2</sup> )flexible with cable end |
| Tightening torque               | < 1.4 N.m screw clamp terminals  |
| Mechanical durability           | 10000 Cycles with GV3P and GV3L<br>30000 cycles with GV2ME and GV2P  |
| Quantity per Set                | Set of 10  |
| Height                          | 3.50 in (89 mm)  |
| Width                           | 0.71 in (18 mm)  |
| Depth                           | 2.60 in (66 mm)  |
| Net Weight                      | 0.23 lb(US) (0.105 kg)   |
| Color                           | Dark grey  |

## Ordering and shipping details

|                   |                                  |
|-------------------|----------------------------------|
| Category          | 22367-MANUAL STR PROTECTOR - GV2 |
| Discount Schedule | I11                              |
| GTIN              | 3389110343694                    |
| Returnability     | No                               |
| Country of origin | CZ                               |

## Packing Units

|                              |                   |
|------------------------------|-------------------|
| Unit Type of Package 1       | PCE               |
| Number of Units in Package 1 | 1                 |
| Package 1 Height             | 3.27 in (8.3 cm)  |
| Package 1 Width              | 1.42 in (3.6 cm)  |
| Package 1 Length             | 3.62 in (9.2 cm)  |
| Package 1 Weight             | 3.95 oz (112.0 g) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

---

GVAS...

