

CH325NR

Safety switch, heavy duty, fusible, 400A, 240 VAC/250VDC, 3 poles, 125 hp, NEMA 3R, neutral



Main

Product	Single Throw Safety Switch
Disconnect Type	Fusible disconnect
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty

Complementary

Line Rated Current	400 A
Factory Installed Neutral	Neutral (factory installed)
Mounting Type	Surface
Voltage Rating	240 V DC 250 V AC
Wire Size	AWG 1/0...750 kcmil copper or aluminium
Maximum Horse Power Rating	50 Hp 240 V AC 50...60 kHz 3 phase NEC 240.6 125 Hp 240 V AC 50...60 kHz 3 phase NEC 430.52 50 hp 250 V DC
Height	50.31 in (1277.87 mm)
Maximum Width	27.88 in (708.15 mm)
Depth	10.13 in (257.30 mm)
Tightening torque	550 lbf.in (62.14 N.m) AWG 1/0...750 kcmil)

Environment

Certifications	CSA
Enclosure Rating	NEMA 3R galvanized steel

Ordering and shipping details

Category	00153 - C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	00785901181934
Nbr. of units in pkg.	1
Package weight(Lbs)	190 lb(US) (86.18 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product