




**ENTRANCE HEADS - ALUMINUM**

Clamp Type for Rigid/IMC or EMT, Aluminum  
N/A

**B78**



Catalog #: 2408

**APPLICATIONS**

For use to bring overhead electrical service into buildings  
N/A

**PRODUCT FEATURES**

Lightweight aluminum body construction eases installation and provides corrosion resistance  
Plastic insuliner snaps out easily for quick cable insertion

**UL LISTED**

Standard 514B, UL Listed E195972, E195973

**GENERAL PRODUCT INFORMATION**

Trade Size: 2 in.

**CONFIGURATION**

Insulating Hole Diameter: 3 Holes 1 in. Dia.; 2 Holes 3/4 in. Dia.; 1 Hole 17/32 in. Dia.

**DRAWING DIMENSIONS**

Dimension A: 6 in.  
Dimension B: 4-1/2 in.  
Dimension C: 4-23/32 in.  
Dimension D: 6-19/32 in.

**PACKAGING**

Package Type: Carton  
Ship Carton Qty.: 5  
Product UPC-A Labeled: Yes  
Weight (Lbs. Per/C): 145.20  
Ship Carton Length (in.): 11.50  
Ship Carton Width (in.): 11.20  
Ship Carton Height (in.): 8.00  
Ctn Weight (Lbs.): 7.26  
UPC Number: 050169024089  
I2of5: 50050169024084