

Product data sheet

Characteristics

8911DPSG33V09

Starter, Definite Purpose, nonreversing, 30A, 3 pole, 3 phase, 208V to 240V AC coil, melting alloy overload, NEMA 1, +options



Main

| | |
|-------------------------|---|
| Product | Definite Purpose Starter |
| Ampere Rating | 30 A |
| Horsepower Rating | 2 Hp 115 V AC, 1 phase 5 Hp 230 V AC, 1 phase 10 Hp 230 V AC, 3 phase 15 Hp 460 V AC, 3 phase 20 hp 575 V AC, 3 phase |
| Maximum Voltage Rating | 600 V AC |
| Control Circuit Voltage | 220 V AC 50 Hz 208...240 V AC 60 Hz |
| Phase | 3 phase |

Complementary

| | |
|-------------------------|--|
| Enclosure Material | Painted sheet steel |
| Enclosure Rating | NEMA 1 |
| Locked Rotor Amperes | 180 A 230 V AC 150 A 460 V AC 120 A 575 V AC |
| Number of Poles | 3P |
| Range | DPS |
| Overload Type | Melting alloy |
| Number of Thermal Units | 3 |

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | 21381-8911 DP |
| Discount Schedule | CP1 |
| GTIN | 785901081524 |
| Returnability | Yes |
| Country of origin | CN |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.60 in (16.764 cm) |
| Package 1 Width | 6.50 in (16.51 cm) |
| Package 1 Length | 17.90 in (45.466 cm) |
| Package 1 Weight | 5.73 lb(US) (2.599 kg) |

Offer Sustainability

| | |
|----------------------------|--|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
