

NMD90 CANADEX® Copper

2C6(7) NMD90 CU CANADEX RED

Contact

Inside Sales Representatives
Phone: 905-944-4300
buildingwire.canada@nexans.com

Nexans Ref.: 12001379

Country Ref.: 649814

EAN 13: 622089106505

Residential cable

DESCRIPTION

CSA File #LL23462 Class 5821 02

Nexans NMD90 CANADEX® Red is a variant of copper conductor NMD90 CANADEX®, with NO WHITE WIRE in the 2 conductor cable. This cable is designed for use on 240-volt systems where there is no NEUTRAL, therefore the cable has a black and a red conductor in addition to the bare bonding wire. To make identification easier it is usually supplied with a RED overall jacket. It should NOT be used on 120 volt systems as there is no neutral, and it is dangerous to use either the red or the black as a neutral. Large sizes are available for use with electric furnaces.

Sizes 4 AWG and larger are twisted.

Nexans NMD90 CANADEX® Jacket Colour: Red

Nexans NMD90 CANADEX® Insulation Colours: Black, Red

Nexans NMD90 CANADEX® Red Applications:

- For open or concealed wiring in dry or damp locations where not exposed to mechanical injury.
- Minimum recommended handling temperature minus 25°C (with suitable handling procedures).
- Maximum conductor temperature 90°C.
- Specifically designed for 240 V heating circuits.

NEW FEATURES now available in sizes 2C12 AWG and 2C14 AWG

Click [here](#) to learn more about the features



STANDARDS

National CSA C22.2 N° 48

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Insulation	PVC/Nylon
Jacket Colour	Red
With Bonding Conductor	Yes
With neutral or not	No

Dimensional characteristics

Approximate net weight	453.2 kg/km
Cable Diameter	9.03 mm
Conductor size (AWG)	6 AWG
Number of cores	2

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 2024-06-12 www.nexans.ca Page 1 / 2

NMD90 CANADEx® Copper

2C6(7) NMD90 CU CANADEx RED

Contact

Inside Sales Representatives
Phone: 905-944-4300
buildingwire.canada@nexans.com

Dimensional characteristics

Number of strands	7
-------------------	---

Electrical characteristics

Maximum operating voltage	300 V
---------------------------	-------

Usage characteristics

Maximum operating temperature	90 °C
-------------------------------	-------

Minimum installation temperature	-25 °C
----------------------------------	--------