

DEK 5/8 MM WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

General ordering data

| | |
|--------------------|--|
| Version | Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white |
| Order No. | 2007130000 |
| Type | DEK 5/8 MM WS |
| GTIN (EAN) | 4050118392012 |
| Qty. | 500 pc(s). |
| compatible printer | 2599430000 2599440000 |

DEK 5/8 MM WS

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Height | 5 mm | Height (inches) | 0.197 inch |
| Width | 8 mm | Width (inches) | 0.315 inch |
| Net weight | 0.147 g | | |

Temperatures

| | |
|-----------------------------|-------------|
| Operating temperature range | -50...90 °C |
|-----------------------------|-------------|

General data

| | | | |
|-----------------------------------|-------------|-----------------------------------|-------------------------|
| Application/manufacture | Weidmueller | Colour | white |
| Halogen | No | Material | PC-ABS, TPU |
| Operating temperature range | -50...90 °C | Operating temperature range, max. | 90 °C |
| Operating temperature range, min. | -50 °C | Orientation of print | horizontal and vertical |
| Printed characters | without | Size of labelling field | 4.5 x 7.5 mm |
| UL 94 flammability rating | V-2 | Version | halogen-free |
| Width | 8 mm | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000761 | ETIM 7.0 | EC000761 |
| ETIM 8.0 | EC000761 | ETIM 9.0 | EC000761 |
| ECLASS 9.0 | 27-14-11-37 | ECLASS 9.1 | 27-14-11-37 |
| ECLASS 10.0 | 27-14-11-37 | ECLASS 11.0 | 27-28-11-01 |
| ECLASS 12.0 | 27-28-11-01 | ECLASS 13.0 | 27-28-11-01 |
| ECLASS 14.0 | 27-28-11-01 | | |

Environmental Product Compliance

| | |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC | No SVHC above 0.1 wt% |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|-----------------------------|--|
| Engineering Data | CAD data – STEP |
| Product Change Notification | MultiMark_PCN_de_Extern MultiMark_PCN_en_external |
| Catalogues | Catalogues in PDF-format |
| Brochures | |

DEK 5/8 MM WS

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Example of use

