

# YCS27R, Aluminum Sleeve, Staked Cable Stop

By Burndy  
Catalog # YCS27R



HYSPLICE AL sleeve with staked cable stop, designed to withstand jumper loop tensile and vibration stresses. ANSI C119.4 CLASS 2 (PARTIAL TENSION), 5-3/4 IN L.

## Application

HYSPLICE sleeve designed to withstand jumper loop tensile and vibration stresses

## General

Catalog Number	YCS27R
Connector Type	Splice
Construction Material - Main	Aluminum
Die Index	247
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YCS-R
UPC	781810015025
UPC 12 Digit	7818100150255

## Dimensions

Dimension - B Length inch	2.81 in
Dimension - L Length Overall mm	146 mm
Dimension - Length Overall inch	5.75 in
Dimension - Outside Diameter inch	0.78 in

## Conductor Related

Conductor - ACSR Str Size	3/0 (6/1) Pigeon AWG;4/0 (6/1) Penquin AWG;80 (8/1)
---------------------------	---

Conductor - ACSR Str Size Range	Grouse kcmil;101.8 (12/7) Petrel kcmil;110.8 (12/7) Minorca kcmil
Conductor - AL Str Size	3/0 (6/1) Pigeon AWG-110.8 (12/7) Minorca kcmil
Conductor - AL Str Size Range	3/0 AWG

## Certifications And Compliance

Buy American Compliant	Contact Manufacturer
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	RUS
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	7400

## Product Assets

- [Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR\\_YCS-R\\_LineArt](#)
- [Sales Drawings - 50115707](#)
- [Specifications - YCS27R](#)