



Pictures for illustration purpose only



## Specifications TLWLC100P

### Electrical Specifications

Model No.	TLWLC100P
Power (W) ± 10%	100 W
Input Voltage (V)	AC100-277V, 50/60Hz
Efficacy	120 lm/W
Power Factor (PF)	0.9

### Photometric Specifications

CRI	80
CCT	5 000 K
Beam angle	360°
Light Output	12 000 lm
Dimmable	No

### Mechanical Specifications

IP Rating	IP65
Material	PC / Aluminum / Stainless steel
Lens	Clear PC
Net Weight	2.27 kg
Product size (mm)	Ø 165 mm x 288 mm
Product size (inch)	± 6.5 po x 11.34 po
Operating Humidity	10% - 90%
Operating Temperature	-40°C ~ 60°C

## Product Description:

1. Stainless steel guard for safety protection. Can be used directly on the floor.
2. Integrated NEMA5-15R receptacle. Can connect in series up to 7 pieces.
3. With approximately 10 ft power cord. (≈ 3 048 mm)
4. Portable hook. Easy to carry and install.
5. Long lifespan up to 50 000 hours.
6. Replacement for 250 W MH traditional temporary lamp.
7. 6 000 V high voltage surge protection.
8. 3 000 K and 4 000 K available on special request.

## Applications:

Construction areas, temporary site, different scale working places, repair workshop, warehouse, indoor and outdoor etc.

Similar Products	Color	W	Lumen
TLWLC60P	5 000 K	60 W	7 200 lm
TLWLC150P	5 000 K	150 W	18 000 lm