



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	User Manual
Number of tare power	3 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

### Physical

Cable length	5 ft (1.52 m)
Depth	4.13 in (10.5 cm)
Height	5.47 in (13.9 cm)
Mounting preference	No preference
Product Weight	7.69 lb(US) (3.49 kg)
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Width	10.79 in (27.4 cm)

### Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA 5-15P
Efficiency at full load	92...139 V
Nominal Input Voltage	120 V

### Output

Kw Rating	330 W
Max Configurable Power (Watts)	330 W
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Nb of power socket outlets	5 NEMA 5-15R 2 NEMA 5-15R surge

Curve equation	Efficiency
Curve fixed loss	0.0087
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0
Curve square loss	0.0038
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data US DOE Test
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	120 V
Maximum configurable power in VA	600 VA
Rated power in VA	600 VA
Transfer Time	6ms typical : 10ms maximum

## Conformance

Product Certifications	California (CEC) Battery Charger CTUVus NOM
Standards	FCC Part 15 class B UL 1778
Equipment protection policy	Lifetime : \$75000

## Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...90 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	35 dBA
Heat dissipation	16 Btu/h
Show note OP temperature	No

## Batteries & Runtime

Battery Type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	10 h
Liquid Electrolyte Value	0
Battery curve	C
Battery Charge Power (Watts)	7 W rated
Battery power in VAH	78 VAh capacity 66 VAh runtime
Battery life	3...5 year(s)
Extendable Run Time	0

## Communications & Management

Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rating	490 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
Let Through Voltage Rating	5 V

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304325116
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

## Packing Units

Package 1 Height	7.72 in (19.6 cm)
Package 1 width	14.29 in (36.3 cm)
Package 1 Length	6.61 in (16.8 cm)
SCC14	10731304325113
Number of Units in Package 2	2
Package 2 Weight	18.52 lb(US) (8.40 kg)
Package 2 Height	8 in (203.20 mm)
Package 2 width	13 in (330.20 mm)
Package 2 Length	14 in (355.60 mm)
Number of Units in Package 3	60
Package 3 Weight	504.86 lb(US) (229 kg)
Package 3 Height	42.05 in (106.8 cm)
Package 3 width	29.80 in (75.7 cm)
Package 3 Length	41.54 in (105.5 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------