


TYPE ILSCONS

Features

- Color coded
- Funnel Entry
- Manufactured from high strength copper alloy
- Electro-tin plated
- Silver solder brazed seam
- Vinyl insulation
- Packaged in convenient small quantities
- Insulated connectors are rated for 600 volts, 90° C

Benefits

- Provides easy wire range identification
#22-16 AWG Red
#16-14 AWG Blue
#12-10 AWG Yellow
- Provides maximum conductivity
- Provides low contact resistance
- May be crimped anywhere and will not split open, even under extreme operating stresses
- Provides tough pliable insulative qualities to protect connectors and wire from corrosion as well as providing some strain relief
- Attractive resealable packaging designed for merchandise racks
- Ensures reliability for copper conductor



Catalog Number	Wire Range	Nema Tab	Length	Maximum Wire Insulated Diameter	Connector Type	Description
45100-B100	16-22	.032 x .250	.807	.145	Female	Vinyl Insulated Disconnects
45100-B1000	16-22	.032 x .250	.807	.145	Female	Vinyl Insulated Disconnects
45101-B100	16-22	.032 x .250	.827	.145	Male	Vinyl Insulated Disconnects
45101-B1000	16-22	.032 x .250	.827	.145	Male	Vinyl Insulated Disconnects
45110-B100	14-16	.032 x .250	.807	.175	Female	Vinyl Insulated Disconnects
45110-B1000	14-16	.032 x .250	.807	.175	Female	Vinyl Insulated Disconnects
45111-B100	14-16	.032 x .250	.827	.175	Male	Vinyl Insulated Disconnects
45111-B1000	14-16	.032 x .250	.827	.175	Male	Vinyl Insulated Disconnects
45120-B50	10-12	.032 x .250	.925	.255	Female	Vinyl Insulated Disconnects
45120-B500	10-12	.032 x .250	.925	.255	Female	Vinyl Insulated Disconnects
45121-B50	10-12	.032 x .250	.945	.255	Male	Vinyl Insulated Disconnects
45121-B500	10-12	.032 x .250	.945	.255	Male	Vinyl Insulated Disconnects

Can be supplied in bulk. Consult factory for part number.

Other sizes available on request. Contact factory for pricing.